

	POWERBANK POWERPLAY-10S-GC 10000 mAh 18 W Green Cell	POWERBANK POWERPLAY-20-GC 20000 mAh 18 W Green Cell	POWERBANK POWERPLAY-20S-BLACK-GC 20000 mAh 22.5 W Green Cell	POWERBANK POWERPLAY-20S-WHITE-GC 20000 mAh 22.5 W Green Cell	PORTABLE POWER STATION TRAVEL-POWERBOX-OPTI-1200 461 Wh 600 W VOLT Polska	PORTABLE POWER STATION TRAVEL-POWERBOX-OPTI-600 230 Wh 300 W VOLT Polska	CHARGER POWERBANK XTAR-PB25 18 W XTAR
							
	21.04 EUR 21.04 EUR	30.64 EUR 30.64 EUR	29.20 EUR 29.20 EUR	29.20 EUR 29.20 EUR	316.65 EUR 316.65 EUR	234.68 EUR 234.68 EUR	18.17 EUR 18.17 EUR
Battery capacity	10000 mAh	20000 mAh	20000 mAh	20000 mAh	461 Wh (20.8 Ah / 22.2 V)	230 Wh (20.8 Ah / 11.1 V)	...
Battery type	...	...	...	...	...	...	Li-Ion 18650, 18700, 20700, 21700 / 2 pcs
Maximal load power	18 W	18 W	22.5 W	22.5 W	600 W	300 W	18 W
Number of inputs	1 pcs (any of the USB-C ports)	1 pcs (any of the USB-C ports)	2 pcs - Charging can be done through the dedicated port or the PD port	2 pcs - Charging can be done through the dedicated port or the PD port	1 pcs	1 pcs	1 pcs
Number of outputs	• 2 pcs USB-C, • 2 pcs USB-A	• 2 pcs USB-C, • 2 pcs USB-A	• 2 pcs USB-C, • 1 pcs USB-A	• 2 pcs USB-C, • 1 pcs USB-A	9 pcs	9 pcs	• 1 pcs USB-C, • 1 pcs USB-A
Power inputs	USB-C socket : 5 V / 3 A ... 9 V / 2 A - 18 W (max)	USB-C socket : 5 V / 3 A ... 9 V / 2 A - 18 W (max)	USB-C1 : 5 V / 3 A ... 9 V / 2 A ... 12 V / 1.5 A - 18 W (max) USB-C2 PD : 5 V / 3 A ... 9 V / 2 A ... 12 V / 1.5 A - 18 W (max)	USB-C1 : 5 V / 3 A ... 9 V / 2 A ... 12 V / 1.5 A - 18 W (max) USB-C2 PD : 5 V / 3 A ... 9 V / 2 A ... 12 V / 1.5 A - 18 W (max)	1 pcs 5.5/2.1 socket, 12 ... 24 V DC / 5.5 A (battery charging)	1 pcs 5.5/2.1 socket, 12 ... 24 V DC / 5.5 A (battery charging)	USB-C socket : 5 V / 2 A ; 9 V / 2 A ; 12 V / 1.5 A - 18 W (max)
Power outputs	• 2 pcs USB-A : 5 V / 3 A ... 9 V / 2 A, 18 W (max) - Ultra Charge, • 2 pcs USB-C : 5 V / 3 A ... 9 V / 2 A, 18 W (max) - PD3.0	• 2 pcs USB-A : 5 V / 3 A ... 9 V / 2 A, 18 W (max) - Ultra Charge, • 2 pcs USB-C : 5 V / 3 A ... 9 V / 2 A, 18 W (max) - PD3.0	• 1 pcs USB-C2 PD : 5 V / 3 A ... 9 V / 2.22 A ... 12 V / 1.67 A, 22.5 W (max) - Power Delivery, • 1 pcs USB-C3 : 5 V / 3 A ... 9 V / 2 A ... 12 V / 1.5 A, 18 W (max) - Ultra Charge, • 1 pcs USB-A : 5 V / 3 A ... 9 V / 2 A ... 12 V / 1.5 A, 18 W (max) - Ultra Charge	• 1 pcs USB-C2 PD : 5 V / 3 A ... 9 V / 2.22 A ... 12 V / 1.67 A, 22.5 W (max) - Power Delivery, • 1 pcs USB-C3 : 5 V / 3 A ... 9 V / 2 A ... 12 V / 1.5 A, 18 W (max) - Ultra Charge, • 1 pcs USB-A : 5 V / 3 A ... 9 V / 2 A ... 12 V / 1.5 A, 18 W (max) - Ultra Charge	• 2 pcs AC - Power socket, CEE 7/3 (Schuko), 2 x 230 V / 50 Hz (Pure Sine Wave), • 3 pcs DC1 - 5.5/2.1 socket, 3 x 12 V / 3 A, • 1 pcs DC2 - Car cigarette lighter socket, 12 V / 10 A, • 1 pcs USB-C, PD3.0 max. 60 W (5, 9, 12, 15, 20 V / 3 A Auto), • 2 pcs USB-A, Quick Charge 3.0 max. 18 W (2 x 5 V / 3 A, 9 V / 2 A, 12 V / 1.5 A)	• 2 pcs AC - Power socket, Universal (with and without PE), 2 x 230 V / 50 Hz (Pure Sine Wave), • 3 pcs DC1 - 5.5/2.1 socket, 3 x 12 V / 3 A, • 1 pcs DC2 - Car cigarette lighter socket, 12 V / 8 A, • 1 pcs USB-C, PD2.0 max. 18 W (5, 9, 12, 15, 20 V / 3 A Auto), • 2 pcs USB-A, 2 x 5 V / 2.4 A	• 1 pcs USB-A : 5 V / 3 A ; 9 V / 2 A ; 12 V / 1.5 A - 18 W (max) - QC 3.0 & PD 3.0, • 1 pcs USB-C : 5 V / 3 A ; 9 V / 2 A ; 12 V / 1.5 A - 18 W (max) - QC 3.0 & PD 3.0
Protections	• Short-circuit • Discharge • Temperature • Input and output voltage matching	• Short-circuit • Discharge • Temperature • Input and output voltage matching	• Short-circuit • Discharge • Temperature • Input and output voltage matching	• Short-circuit • Discharge • Temperature • Input and output voltage matching	• Short-circuit • Overload • Overvoltage • Discharge • Temperature	• Short-circuit • Overload • Overvoltage • Discharge • Temperature	• Overcharge protection • Discharge • Overload • Overvoltage • Short-circuit
Color	...	...	Black	White	...	...	...
Main features	• Pass-Through - simultaneous powering of connected devices and charging the battery • Li-Poly battery • Battery status indicator - 4 x LED	• Pass-Through - simultaneous powering of connected devices and charging the battery • Li-Poly battery • Battery status indicator - 4 x LED • Compatible with Quick Charge 3.0, Samsung AFC, Huawei FCP, Apple 2.4A, Mediatek Pump Express 1.1/2.0, USB DCP	• Pass-Through - simultaneous powering of connected devices and charging the battery • Li-Poly battery • Battery status indicator - 4 x LED • Compatible with Power Delivery 2.0 / 3.0, Quick Charge 2.0 / 3.0, PPS, FCP / AFC / SFCP, Mediatek Pump Express 1.1 / 2.0, USB-C DRP	• Pass-Through - simultaneous powering of connected devices and charging the battery • Li-Poly battery • Battery status indicator - 4 x LED • Compatible with Power Delivery 2.0 / 3.0, Quick Charge 2.0 / 3.0, PPS, FCP / AFC / SFCP, Mediatek Pump Express 1.1 / 2.0, USB-C DRP	• Li-Ion battery • Large, readable LCD display with backlight • One-touch action buttons • White light (LED) illuminator built-in 2 W - lighting brightness control (3 levels) + SOS • Fan cooler built-in • Battery charging ≥ 800 cycles • Automatic power-off	• Li-Ion battery • Large, readable LCD display with backlight • One-touch action buttons • White light (LED) illuminator built-in 2 W - lighting brightness control (3 levels) + SOS • Fan cooler built-in • Battery charging ≥ 800 cycles • Automatic power-off	• Charging Li-ion batteries controlled by a three-stage processor TC/CV/CV charging process • Battery status indicator • Battery status indicator LED
Power supply	...	...	...	...	• 19 V DC / 4.73 A (power adapter included) • 12 ... 24 V DC / 5.5 A - Car lighter plug (cable included) • 13 ... 24 V DC - Solar Panel 60 ... 100 W (cable included)	• 19 V DC / 3 A (power adapter included) • 12 ... 24 V DC / 5.5 A - Car lighter plug (cable included) • 13 ... 24 V DC - Solar Panel 60 ... 100 W (cable included)	...
Charging time (recover to 100% capacity)	...	...	...	...	5 ... 7 h	4 ... 5.5 h	...
Operation temp	...	...	...	...	0 °C ... 40 °C	0 °C ... 35 °C	...
Weight	0.2 kg	0.35 kg	0.35 kg	0.35 kg	4.94 kg	2.75 kg	0.2 kg
Dimensions	140 x 72 x 14 mm	140 x 72 x 25 mm	140 x 72 x 25 mm	140 x 72 x 25 mm	290 x 164 x 235 mm	230 x 120 x 200 mm	140 x 72 x 14 mm
Manufacturer / Brand	Green Cell	Green Cell	Green Cell	Green Cell	VOLT Polska	VOLT Polska	XTAR
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years	2 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00