

	LOCK MODULAR CYLINDER GERDA SLR/G06130/A Tedee GERDA	LOCK MODULAR CYLINDER GERDA SLR/G0613768/C Tedee GERDA	WIFI/BLEETOOTH BRIDGE TEDEE-BRIDGE Tedee GERDA	SMART DOOR LOCK TEDEE-GO/GC Bluetooth, Tedee GERDA	SMART DOOR LOCK TEDEE-GO/SR Bluetooth, Tedee GERDA	WIRELESS KEYPAD TEDEE-KEYBOARD Bluetooth, Tedee GERDA	SMART DOOR LOCK TEDEE-PRO/GC Bluetooth, Tedee GERDA	SMART DOOR LOCK TEDEE-PRO/SR Bluetooth, Tedee GERDA
	57.72 EUR 57.72 EUR	57.72 EUR 57.72 EUR	76.34 EUR 76.34 EUR	196.33 EUR 196.33 EUR	196.33 EUR 196.33 EUR	113.58 EUR 113.58 EUR	382.51 EUR 382.51 EUR	382.51 EUR 382.51 EUR
Application	TEDEE-PRO	TEDEE-PRO	TEDEE-GO, TEDEE-PRO	opening and closing the lock	opening and closing the lock	TEDEE-GO, TEDEE-PRO	opening and closing the lock	opening and closing the lock
Dimension A (inside part)	30 ... 61 mm	30 ... 61 mm
Dimension B (outside part)	30 mm	37 ... 68 mm
Compatible lock type	European	European	...	<ul style="list-style-type: none"> European cylinder with emergency function Adaptor available : Nordic, American 	<ul style="list-style-type: none"> European cylinder with emergency function Adaptor available : Nordic, American 	...	<ul style="list-style-type: none"> Dedicated cylinders of the Gerda SLR series, European cylinder with emergency function Adaptor available : Nordic, American, European 	<ul style="list-style-type: none"> Dedicated cylinders of the Gerda SLR series, European cylinder with emergency function Adaptor available : Nordic, American, European
Wireless	<ul style="list-style-type: none"> Bluetooth, 2.4 GHz - BLE 5.0, Wi-Fi 2.4 GHz, 5 GHz 	Bluetooth, 2.4 GHz - BLE 5.0	Bluetooth, 2.4 GHz - BLE 5.0	Bluetooth, 2.4 GHz - BLE 5.0	Bluetooth, 2.4 GHz - BLE 5.0	Bluetooth, 2.4 GHz - BLE 5.0
Spacers	6 mm, 10 mm, 15 mm	2 x 6 mm, 2 x 10 mm, 2 x 15 mm
Mobile phones support	<ul style="list-style-type: none"> The Tedee free application on Android The Tedee free application on iOS 	<ul style="list-style-type: none"> The Tedee free application on Android The Tedee free application on iOS 	...	<ul style="list-style-type: none"> The Tedee free application on Android The Tedee free application on iOS 	<ul style="list-style-type: none"> The Tedee free application on Android The Tedee free application on iOS
Power consumption	1.5 W
Main features	<ul style="list-style-type: none"> Modular construction Adjustable cylinder length Anti-drilling protection design In the kit : 3 keys, code card A type - Cam Class of protection 6 acc. to PN-EN 1303:2015-07 	<ul style="list-style-type: none"> Modular construction Adjustable cylinder length Anti-drilling protection design In the kit : 3 keys, code card C type - Cam Class of protection 6 acc. to PN-EN 1303:2015-07 	<ul style="list-style-type: none"> Remote control and management Bi-directional encrypted radio communication : TLS 1.3 Secure virtual key - 256-bit data encryption Remote opening of the door lock button Opening the door : manual, lock button, Tedee application 3 levels of access, password-protected Compatibility with many smart home systems (e.g. Apple HomeKit, Google Assistant, Amazon Alexa, Homey, Fibaro, Grenton, eeDomus, Consolomio) LED indication Assembly max. 2 m from Tedee lock, 1 ... 10 m from Wi-Fi router 	<ul style="list-style-type: none"> Remote control and management - Tedee application : remote access, Phone notification, Activity log, auto-open and close, Setting scenarios by different events, voice control Bi-directional encrypted radio communication : TLS 1.3 Secure virtual key - 256-bit data encryption Remote opening of the door lock button Opening the door : manual, lock button, Tedee application 3 levels of access, password-protected Compatibility with many smart home systems (e.g. Apple HomeKit, Google Assistant, Amazon Alexa, Homey, Fibaro, Grenton, eeDomus, Consolomio) LED indication Full compatibility with inward-opening doors Compatibility with outward-opening doors : min. 40 mm (the distance between the cylinder axis and the door frame) 	<ul style="list-style-type: none"> Remote control and management - Tedee application : remote access, Phone notification, Activity log, auto-open and close, Setting scenarios by different events, voice control Bi-directional encrypted radio communication : TLS 1.3 Secure virtual key - 256-bit data encryption Remote opening of the door lock button Opening the door : manual, lock button, Tedee application 3 levels of access, password-protected Compatibility with many smart home systems (e.g. Apple HomeKit, Google Assistant, Amazon Alexa, Homey, Fibaro, Grenton, eeDomus, Consolomio) LED indication Assembly max. 2 m from Tedee lock, max. 2 m from Tedee bridge 	<ul style="list-style-type: none"> Remote control and management - Tedee application : remote access, Phone notification, Activity log, auto-open and close, Setting scenarios by different events, voice control Bi-directional encrypted radio communication : TLS 1.3 Secure virtual key - 256-bit data encryption Remote opening of the door lock button Opening the door : manual, lock button, Tedee application 3 levels of access, password-protected Compatibility with many smart home systems (e.g. Apple HomeKit, Google Assistant, Amazon Alexa, Homey, Fibaro, Grenton, eeDomus, Consolomio) LED indication Full compatibility with inward-opening doors Compatibility with outward-opening doors : min. 30 mm (the distance between the cylinder axis and the door frame) built-in battery Low battery level alarm - Tedee application Charging via USB cable with micro USB magnetic adapter Battery charge indicator - Tedee application 	<ul style="list-style-type: none"> Remote control and management - Tedee application : remote access, Phone notification, Activity log, auto-open and close, Setting scenarios by different events, voice control Bi-directional encrypted radio communication : TLS 1.3 Secure virtual key - 256-bit data encryption Remote opening of the door lock button Opening the door : manual, lock button, Tedee application 3 levels of access, password-protected Compatibility with many smart home systems (e.g. Apple HomeKit, Google Assistant, Amazon Alexa, Homey, Fibaro, Grenton, eeDomus, Consolomio) LED indication Full compatibility with inward-opening doors Compatibility with outward-opening doors : min. 30 mm (the distance between the cylinder axis and the door frame) built-in battery Low battery level alarm - Tedee application Charging via USB cable with micro USB magnetic adapter Battery charge indicator - Tedee application 	
Power supply	5 V / 300 mA - USB socket (power adapter included), micro USB socket	3 x Battery CRI123A 3 V (included)	3 x Battery CRI123A 3 V (included)	3 x 1.5V, type AAA/LR03 battery	Li-Poly battery 3000 mAh - Charging via micro USB port	Li-Poly battery 3000 mAh - Charging via micro USB port
Backup time	6 ... 8 months	6 ... 8 months	...	6 ... 10 months	6 ... 10 months
Housing	Plastic	Plastic (ABS)	Plastic (ABS)	Plastic	Aluminum	Aluminum
"Index of Protection"	IP20	IP20	IP65	IP20	IP20
Color	White	Graphite + Black	Silver + White	Gray	Graphite + Black	Silver + White
Operation temp	10 °C ... 40 °C	10 °C ... 40 °C	10 °C ... 40 °C	-30 °C ... 60 °C	10 °C ... 40 °C	10 °C ... 40 °C
Permissible relative humidity	max. 65 %	max. 65 %	max. 65 %	max. 95 %	max. 65 %	max. 65 %
Weight	0.052 kg	0.232 kg	0.232 kg	0.16 kg	0.196 kg	0.196 kg
Dimensions	64 x 64 x 28 mm	Ø 58 x 65 mm	Ø 58 x 65 mm	135 x 48 x 28 mm	<ul style="list-style-type: none"> Ø 45 x 56 mm 2 m - Length of the cable 	<ul style="list-style-type: none"> Ø 45 x 56 mm 2 m - Length of the cable
Manufacturer / Brand	GERDA / Tedee	GERDA / Tedee	GERDA / Tedee	GERDA / Tedee	GERDA / Tedee	GERDA / Tedee	GERDA / Tedee	GERDA / Tedee
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00