


Code: LNA-177

ANTENNA PREAMPLIFIER **LNA-177** 5-48 28dB

Net: **7.56 USD** Gross: **7.56 USD**




Broadband board amplifier to antenna box.

SPECIFICATION


Range:	174 MHz ... 694 MHz
Channels:	5 - 12 , 21 - 48
Gain :	14 ... 28 dB
Gain K5 - K12:	14 dB ... 15 dB (increasing)
Gain K21 - K48:	22 dB ... 28 dB (increasing)
Number of outputs [connectors type]:	1 pcs (F connector)
Number of inputs [connectors type]:	1 pcs (antenna terminals)
Maximum output level:	98 dBμV
Ripples:	• ≤ 3 dB @ 174 ... 230 MHz • ≤ 2.8 dB @ 470 ... 694 MHz
Input/output impedance:	300 Ω / 75 Ω
Main features:	Built-in GSM / LTE filter
Power supply:	12 V / 55 mA via antenna cable
Shielding:	✓
Operation temp:	-30 °C ... 55 °C
Weight:	0.024 kg
Dimensions:	55 x 40 x 12 mm
Guarantee:	2 years

PRESENTATION

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Amplitude - frequency response:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------