

Code: FAAC-XP20WD

PHOTOCELL **FAAC-XP20WD** TXRX SET

Net: **114.98 EUR** Gross: **114.98 EUR**



Photocells are designed for cooperation with gate automation systems. Wireless. The photocells have the ability to adjust the angle horizontally. The set includes transmitter and receiver.

An infra-red beam is sent to the receiver from the transmitter. If an object appears in the field of the created barrier (eg a car or a man), the photocell will react by sending a signal to change the state at the control unit input.

The devices are resistant to moisture penetration, equipped with a housing that protects against unwanted exposure to sunlight.

SPECIFICATION

Beam width:	$\pm 7^\circ @ 20 \text{ m}$, $\pm 13.5^\circ @ 5 \text{ m}$
Operation range:	<ul style="list-style-type: none">• 20 m,• 10 m Battery
Response time:	40 ms
Power supply:	<ul style="list-style-type: none">• 12 ... 24 V AC/DC / Battery : 3 V CR2 (not included) Transmitter,• 12 ... 24 V AC/DC Receiver
Current consumption:	<ul style="list-style-type: none">• 5 mA @ 24 V DC / 40 μA Battery Transmitter• 30 mA Receiver
Number of relay outputs:	1
Output:	1 x NC
Main features:	<ul style="list-style-type: none">• Cooperation with the FAAC gate automation system• Angle adjustment range $\pm 90^\circ$ horizontal,• Wireless - 4 Channels,• Possibility to install up to 4 pairs of photocells on the same automation system• Protection from interference produced by external light sources (such as vehicle LED headlights)• Surface/column mounting• Immunity to environmental changes
Housing:	Plastic
"Index of Protection":	IP54
Color:	Black
Operation temp:	-20 $^\circ$ C ... 55 $^\circ$ C

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Weight:	<ul style="list-style-type: none"> • 0.070 kg Transmitter • 0.076 Receiver
Dimensions:	130 x 42 x 41 mm Transmitter / Receiver
Manufacturer / Brand:	FAAC
Guarantee:	2 years

PRESENTATION

Front view:



Internal view of the housing:





Mounting side view:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------