





	SET OF LED LUMINAIRES ZSO-01/3000 ZAMEL	SET OF LED LUMINAIRES ZSO-01/4000 ZAMEL	KIT ZSW-01 SUPLA ZAMEL	KIT ZSW-02 SUPLA ZAMEL
				
	878.33 SEK 878.33 SEK	878.33 SEK 878.33 SEK	4846.53 SEK 4846.53 SEK	4311.11 SEK 4311.11 SEK
Support	SUPLA	SUPLA	SUPLA	SUPLA
Wireless	Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n	Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n	Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n	Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n
Mobile phones support	<ul style="list-style-type: none"> The SUPLA free application on Android The SUPLA free application on iOS 	<ul style="list-style-type: none"> The SUPLA free application on Android The SUPLA free application on iOS 	<ul style="list-style-type: none"> The SUPLA free application on Android The SUPLA free application on iOS 	<ul style="list-style-type: none"> The SUPLA free application on Android The SUPLA free application on iOS
Main features	<ul style="list-style-type: none"> Control from a Web browser, Local control by physical button, schedule, timer, remote access, voice control, Possibility to manually program scenarios from the built-in API 	<ul style="list-style-type: none"> Control from a Web browser, Local control by physical button, schedule, timer, remote access, voice control, Possibility to manually program scenarios from the built-in API 	<ul style="list-style-type: none"> Control from a Web browser, Local control by physical button, schedule, timer, remote access, voice control, Possibility to manually program scenarios from the built-in API 	<ul style="list-style-type: none"> Control from a Web browser, Local control by physical button, schedule, timer, remote access, voice control, Possibility to manually program scenarios from the built-in API
Housing	Plastic	Plastic	Plastic	Plastic
Color	Green	Green
Guarantee	2 years	2 years	2 years	2 years
Manufacturer / Brand	ZAMEL	ZAMEL	ZAMEL	ZAMEL
Light color	Warm - 3000 K Warm - 3000 K	Neutral - 4000 K Neutral - 4000 K
Illumination angle	120 ° 120 °	120 ° 120 °
Seating depth of the luminaire	38 mm 38 mm	38 mm 38 mm
Number of pins	2 x NO
Relay maximal load	2 x 5 A @ 250 V AC 5 A @ 250 V AC	2 x 5 A @ 250 V AC
Montage hole diameter	Ø 75 mm ... 80 mm Ø 75 mm ... 80 mm	Ø 75 mm ... 80 mm Ø 75 mm ... 80 mm
Power voltage	24 V DC 24 V AC	24 V DC 24 V AC	230 V AC 24 V AC/DC	230 V AC
Current consumption	350 lm / 3.5 W 350 lm / 3.3 W	350 lm / 3.5 W 350 lm / 3.3 W
Material	Plastic	Plastic

Number of elements	8 3 3	8 3 3	7 6 1	7 3 3 1
Application	Lighting control	Lighting control	roller shutters, roof windows, awnings, drop-down screens, curtains swing gates, sliding gates, garage gates, doors	roller shutters, roof windows, awnings, drop-down screens, curtains Lighting control, switching devices on/off Works with LED lighting - (RGB) 12-24V LED strips
Rated voltage	230 V AC 12 ... 24 V DC
Maximal total load	1250 VA 140 W
Total maximal current	5 A 6 A (2 A / Channel)
Maximal outputs load	350 W	350 W • 750 W (single output) - light bulbs and halogen lamps • 250 W (single output) - CFL fluorescent lamps • 60 W (single output) - LED bulbs LED RGB 12 V : 5 m - 70 W LED RGB 24 V : 10 m - 140 W
Number of inputs	1 pcs 1	1 pcs 1	2 pcs 2	2 pcs 2 1
Number of outputs	1 pcs	1 pcs	1 pcs (Motor) 1	1 pcs (Motor) 3
Connector type	screw terminals screw terminals screw terminals	screw terminals screw terminals screw terminals	screw terminals screw terminals screw terminals	screw terminals screw terminals screw terminals screw terminals
"Index of Protection"	IP20 IP44	IP20 IP44	IP20 IP20	IP20 IP20 IP20
Operation temp	-10 °C ... 55 °C	-10 °C ... 55 °C	-10 °C ... 55 °C -20 °C ... 50 °C	-10 °C ... 55 °C -10 °C ... 55 °C -20 °C ... 50 °C
Weight	0.079 kg 0.068 kg 0.019 kg	0.079 kg 0.068 kg 0.019 kg	0.410 kg 0.030 kg 0.034 kg	0.407 kg 0.030 kg 0.04 kg 0.030 kg
Dimensions	78 x 73 x 40 mm 78 x 72 x 35 mm Ø 105 x 7 mm	78 x 73 x 40 mm 78 x 72 x 35 mm Ø 105 x 7 mm	47 x 47 x 20 mm 47 x 47 x 20 mm	47 x 47 x 20 mm 47 x 47 x 20 mm 47 x 47 x 20 mm

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00