















	SINGLE SOCKET WITH LUNGTION BOX 2K58X08/GN-230/EPN 250 V AC 16 A IP54 Elektro-Plast	SINGLE SURFACE SOCKET OUTLET AQUANT-GLEFPN 230 V AC 16 A IP65 Elektro-Plast	DOUBLE SURFACE SOCKET OUTLET AQUANT-G2V1/EPN 230 V AC 16 A IP65 Elektro-Plast	DOUBLE SURFACE SOCKET OUTLET AQUANT-G2V2/EPN 230 V AC 16 A IP65 Elektro-Plast	TRIPLE SURFACE SOCKET OUTLET AQUANT-G3/EPN 230 V AC 16 A IP65 Elektro-Plast	SINGLE SURFACE SOCKET OUTLET ATLO-S1HP5 IP55	SINGLE SURFACE SOCKET OUTLET ATLO-S1HP IP66	DOUBLE SURFACE SOCKET OUTLET ATLO-S2HP IP66	SINGLE SURFACE SOCKET OUTLET BERG/G3733-00/EPN 250 V 16 A Elektro-Plast	DOUBLE SURFACE SOCKET OUTLET BERG/G743-00/EPN 250 V 16 A Elektro-Plast	SINGLE SURFACE SOCKET OUTLET HERMES/0371-09/EPN 250 V AC 16 A IP44 Elektro-Plast	DOUBLE SURFACE SOCKET OUTLET HERMES/0372-09/EPN 250 V AC 16 A IP44 Elektro-Plast	SINGLE SURFACE SOCKET OUTLET LE-282375-FORIX 230 V 16 A IP44 LEGRAND	DOUBLE SURFACE SOCKET OUTLET LE-282377-FORIX 230 V 16 A IP44 LEGRAND
														
	6.72 EUR 6.72 EUR	9.81 EUR 9.81 EUR	16.20 EUR 16.20 EUR	16.72 EUR 16.72 EUR	20.55 EUR 20.55 EUR	5.60 EUR 5.60 EUR	7.83 EUR 7.83 EUR	11.91 EUR 11.91 EUR	2.31 EUR 2.31 EUR	3.33 EUR 3.33 EUR	3.33 EUR 3.33 EUR	5.75 EUR 5.75 EUR	4.78 EUR 4.78 EUR	9.67 EUR 9.67 EUR
Number of intakes	4 pcs Ø 20 mm													
Rated voltage	250 V AC	230 V AC	230 V AC	230 V AC	230 V AC	220 ... 240 V, 50 / 60 Hz	220 ... 240 V, 50 / 60 Hz	220 ... 240 V, 50 / 60 Hz	250 V / 50 Hz	250 V / 50 Hz	250 V AC	250 V AC	230 V / 50 Hz	230 V / 50 Hz
Maximal total load						3840 W	3840 W	3840 W						
Maximal current load	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A
Total maximal current						16 A	16 A	16 A						
Electrical cable													max. 3 x 2.5 mm²	max. 3 x 2.5 mm²
Number of outlets						1 pcs	1 pcs	2 pcs						
Cable terminals	screw terminals	screw terminals	screw terminals	screw terminals	screw terminals				screw terminals	screw terminals	screw terminals	screw terminals	screw terminals	screw terminals
Application									Berg product series	Berg product series				
Grounding	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Socket type	CEE 7/5, Surface-mounted	CEE 7/5, Surface-mounted	2 x CEE 7/5, Surface-mounted	2 x CEE 7/5, Surface-mounted	3 x CEE 7/5, Surface-mounted	CEE 7/3 (Schuko)	CEE 7/3 (Schuko)	CEE 7/3 (Schuko)	1 x CEE 7/5, Surface-mounted	2 x CEE 7/5, Surface-mounted	CEE 7/5, Surface-mounted	2 x CEE 7/5, Surface-mounted	CEE 7/5, Surface-mounted	2 x CEE 7/5, Surface-mounted
Protection shutter	✓	✓	✓	✓	✓								✓	✓
Assembly	Mounting screws	Mounting screws	Mounting screws	Mounting screws	Mounting screws				Mounting with screws	Mounting with screws	Mounting screws	Mounting screws	Mounting screws	Mounting screws
"Index of Protection"	IP54	IP65	IP65	IP65	IP65	IP55	IP66	IP66	IP20	IP20	IP44	IP44	IP44	IP44
IK rating	IK07	IK07	IK07	IK07	IK07								IK07	IK07
Housing						Plastic	Plastic	Plastic	Plastic (PA)	Plastic (PA)				
Operation temp						-20 °C ... 60 °C	-20 °C ... 60 °C	-20 °C ... 60 °C						
Main features	<ul style="list-style-type: none"> • Hermetic casing • PN-EN 60670-22:2021 compliance 	<ul style="list-style-type: none"> • UV radiation resistance • Current paths shutters • Additional protection integrated with the base in the form of movable rubber glands • PN-EN-60669-1:2006 compliance 	<ul style="list-style-type: none"> • UV radiation resistance • Current paths shutters • Additional protection integrated with the base in the form of movable rubber glands • PN-EN-60669-1:2006 compliance 	<ul style="list-style-type: none"> • UV radiation resistance • Current paths shutters • Additional protection integrated with the base in the form of movable rubber glands • Vertical layout • PN-EN-60669-1:2006 compliance 	<ul style="list-style-type: none"> • UV radiation resistance • Current paths shutters • Additional protection integrated with the base in the form of movable rubber glands • PN-EN-60669-1:2006 compliance 			Current paths shutters	PN-EN-60669-1:2006 compliance	PN-EN-60669-1:2006 compliance	<ul style="list-style-type: none"> • Hermes product series • Splash-proof casing • opening lid • For indoor use • For outdoor use • PN-EN 60884-1:2006 compliance 	<ul style="list-style-type: none"> • Hermes product series • Splash-proof casing • opening lid • For indoor use • For outdoor use • PN-EN 60884-1:2006 compliance 	Forix product series	Forix product series
Color	Gray	Gray RAL7035	Gray RAL7035	Gray RAL7035	Gray RAL7035	White	Gray	Gray	White - RAL9003	White (RAL 9003)	Black	Black	White - RAL9003	White - RAL9003
Weight	0.13 kg	0.152 kg	0.27 kg	0.3 kg	0.41 kg	0.138 kg	0.400 kg	0.625 kg	0.06 kg	0.100 kg	0.094 kg	0.114 kg	0.212 kg	0.212 kg
Dimensions	120 x 99 x 57 mm	76 x 81 x 56 mm	153 x 81 x 56 mm	76 x 163 x 56 mm	230 x 81 x 56 mm	85 x 70 x 65 mm	165 x 113 x 113 mm	165 x 171 x 113 mm	62 x 62 x 36 mm	104 x 62 x 40 mm	65 x 75 x 48 mm	120 x 75 x 48 mm	69 x 69 x 54 mm	140 x 69 x 54 mm
Manufacturer / Brand	Elektro-Plast	Elektro-Plast	Elektro-Plast	Elektro-Plast	Elektro-Plast	ATLO	ATLO	ATLO	Elektro-Plast Nasielsk	Elektro-Plast Nasielsk	Elektro-Plast Nasielsk	Elektro-Plast Nasielsk	LEGRAND	LEGRAND
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	5 years	5 years	5 years	5 years	2 years	2 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00