

	SMART ACTION TRIGGER ACTIONBOX/S/BLERBOX W-FL 230 V AC	SMART ACTION TRIGGER ACTIONBOX/BLERBOX W-FL 230 V AC	SMART LIGHTING DIMMER DIMMERBOX-V2/BLERBOX W-FL 230 V AC	SMART DOOR AND PEDESTRIAN DOOR CONTROLLER DOORBOX/BLERBOX W-FL 12...24 V DC/AC	SMART GATE AND DOOR CONTROLLER GATEBOX-FR/BLERBOX W-FL 12...24 V DC/AC	SMART GATE AND DOOR CONTROLLER GATEBOX-D/BLERBOX W-FL 12...24 V DC/AC	SMART ACTION TRIGGER INBOX/BLERBOX W-FL CR123A	PARKING SENSOR LED LIGHTING CONTROLLER PARKING-SENSOR/BLERBOX 2...24 V DC	SMART PROXIMITY ACTION TRIGGER PROXIBOX/BLERBOX W-FL 12...24 V DC	SMART PROXIMITY SWITCH PROXISWITCH-V2/BLERBOX 12...24 V DC	SMART ROLLER GATE CONTROLLER ROLLERBOX/BLERBOX W-FL 230 V AC	SMART CONTROLLER FOR ROLLER SHUTTERS SHUTTERBOX-D/BLERBOX W-FL 230 V AC	SMART CONTROLLER FOR ROLLER SHUTTERS SHUTTERBOX-D/BLERBOX W-FL 230 V AC	SMART CONTROLLER FOR ROLLER SHUTTERS SHUTTERBOX-D/BLERBOX W-FL 230 V AC	DUAL SMART SWITCH SWITCHBOX-D-DIN/BLERBOX W-FL 230 V AC	DUAL SMART SWITCH SWITCHBOX-D/BLERBOX W-FL 230 V AC	SMART SWITCH SWITCHBOX-D/BLERBOX W-FL 12 / 24 V DC	SMART SWITCH SWITCHBOX-DIN/BLERBOX W-FL 230 V AC	SMART SWITCH SWITCHBOX-LIGHT/BLERBOX W-FL 230 V AC	TRIPLE SMART SWITCH SWITCHBOX-T-PRO/BLERBOX W-FL 230 V AC	SMART SWITCH SWITCHBOX-V/BLERBOX W-FL 230 V AC	SMART THERMOSTAT THERMOBOX/BLERBOX W-FL 230 V AC	REMOTE CONTROL SREMOT/BLERBOX W-FL	4-CHANNEL REMOTE CONTROL LREMOTE-BASIC/BLERBOX W-FL	4-CHANNEL REMOTE CONTROL LREMOTE-FR/BLERBOX W-FL
Number of channels	22.19 EUR	24.86 EUR	40.91 EUR	38.17 EUR	62.44 EUR	44.82 EUR	22.51 EUR	29.17 EUR	24.86 EUR	13.51 EUR	87.89 EUR	36.99 EUR	46.78 EUR	36.99 EUR	42.88 EUR	37.00 EUR	24.47 EUR	46.78 EUR	24.86 EUR	74.19 EUR	36.99 EUR	52.66 EUR	27.40 EUR	29.17 EUR	33.08 EUR
Application	controlling devices, triggering actions	controlling devices, triggering actions	lighting brightness control	doors, pedestrian doors, lockers, drawers	swing gates, sliding gates, garage gates, doors	swing gates, sliding gates, garage gates, doors	controlling devices, triggering actions	It shows the distance between the moving object and the sensor by using LED lighting • Works with LED lighting - RGB 7-24V LED strips	Non-contact switching on and off, controlling devices, triggering actions	Non-contact switching on and off	roller gates	roller shutters, roof windows, awnings, drop-down screens, curtains	roller shutters, roof windows, awnings, drop-down screens, curtains	roller shutters, roof windows, awnings, drop-down screens, curtains	switching devices on/off	switching devices on/off	switching devices on/off	switching devices on/off	switching devices on/off	switching devices on/off	switching devices on/off	switching heating devices on/off
Power supply	
Rated voltage	230 V AC	230 V AC	230 V AC	12 ... 24 V DC/AC	12 ... 24 V DC/AC	12 ... 24 V DC/AC	3 V - Battery type CR123A	7 ... 24 V DC	12 ... 24 V DC	12 ... 24 V DC	230 V AC	12 ... 24 V DC	230 V AC	230 V AC	230 V AC	230 V AC	12 / 24 V DC	230 V AC	230 V AC	230 V AC	230 V AC	230 V AC	230 V AC	230 V AC	
Operation range	
Maximal total load	• 250 W (resistance load), • 30 W (inductive or capacitive load - e.g. LED lamp)	1150 W / 1150 VA	56 ... 192 W	...	120 W	2 x 1250 VA	...	2 x 1150 W (resistance load) / 2 x 150 W (inductive or capacitive load)	1150 VA	2 x 1150 W (resistance load) / 2 x 1150 W / 1150 VA	...	3680 W (resistance load) / 500 W (inductive or capacitive load)	1150 W / 1150 VA	...	• 3 x 3680 W (resistance load) - AC, • 3 x 500 W (inductive or capacitive load) - AC, • 3 x 380 W - DC	3500 W / 3680 VA	3680 W / 3680 VA	
Total maximal current	1.1 A	5 A	20 mA / Control output	20 mA / Control output	...	8 A	...	5 A	2 x 5 A	...	• 4.5 A (max) • 3 A @ 180 s @ 200 g - Thermal protection	2 x 5 A	2 x 5 A	...	16 A	5 A	...	3 x 16 A	16 A	16 A	
Number of inputs	1	4	2	3	2	2	4	0	0	0	2	2	2	2	2	2	1	2	1	3	1	1	
Number of outputs	0	0	1	1	2	2	0	4	0	1	2	2	2	2	2	2	1	1	1	3	1	1	
Connector type	screw terminals	screw terminals	screw terminals	screw terminals	screw terminals	screw terminals	Connection cube, screw terminals	screw terminals	screw terminals (power)	screw terminals	screw terminals	screw terminals	screw terminals	screw terminals	screw terminals	screw terminals	screw terminals	screw terminals	screw terminals	screw terminals	screw terminals	screw terminals	
Wireless	Wi-Fi, 2.4 GHz - IEEE 802.11g	Wi-Fi, 2.4 GHz - IEEE 802.11g	Wi-Fi, 2.4 GHz - IEEE 802.11g	Wi-Fi, 2.4 GHz - IEEE 802.11g	Wi-Fi, 2.4 GHz - IEEE 802.11g	Wi-Fi, 2.4 GHz - IEEE 802.11g	Wi-Fi, 2.4 GHz - IEEE 802.11g	...	Wi-Fi, 2.4 GHz - IEEE 802.11g	...	Wi-Fi, 2.4 GHz - IEEE 802.11g	Wi-Fi, 2.4 GHz - IEEE 802.11g	Wi-Fi, 2.4 GHz - IEEE 802.11g	Wi-Fi, 2.4 GHz - IEEE 802.11g	Wi-Fi, 2.4 GHz - IEEE 802.11g	Wi-Fi, 2.4 GHz - IEEE 802.11g	Wi-Fi, 2.4 GHz - IEEE 802.11g	Wi-Fi, 2.4 GHz - IEEE 802.11g	Wi-Fi, 2.4 GHz - IEEE 802.11g	Wi-Fi, 2.4 GHz - IEEE 802.11g	Wi-Fi, 2.4 GHz - IEEE 802.11g	Wi-Fi, 2.4 GHz - IEEE 802.11g	Wi-Fi, 2.4 GHz - IEEE 802.11g	Wi-Fi, 2.4 GHz - IEEE 802.11g	
Mobile phones support	• The wBox free application on Android • The wBox free application on iOS	• The wBox free application on Android • The wBox free application on iOS	• The wBox free application on Android • The wBox free application on iOS	• The wBox free application on Android • The wBox free application on iOS	• The wBox free application on Android • The wBox free application on iOS	• The wBox free application on Android • The wBox free application on iOS	• The wBox free application on Android • The wBox free application on iOS	...	• The wBox free application on Android • The wBox free application on iOS	...	• The wBox free application on Android • The wBox free application on iOS	• The wBox free application on Android • The wBox free application on iOS	• The wBox free application on Android • The wBox free application on iOS	• The wBox free application on Android • The wBox free application on iOS	• The wBox free application on Android • The wBox free application on iOS	• The wBox free application on Android • The wBox free application on iOS	• The wBox free application on Android • The wBox free application on iOS	• The wBox free application on Android • The wBox free application on iOS	• The wBox free application on Android • The wBox free application on iOS	• The wBox free application on Android • The wBox free application on iOS	• The wBox free application on Android • The wBox free application on iOS	• The wBox free application on Android • The wBox free application on iOS	• The wBox free application on Android • The wBox free application on iOS	• The wBox free application on Android • The wBox free application on iOS	• The wBox free application on Android • The wBox free application on iOS
Main features	• Local control by physical button • schedule, • timer, • remote access, • voice control, • µWiFi technology support	• Local control by physical button • schedule, • timer, • remote access, • voice control, • µWiFi technology support	• Local control by physical button, • schedule, • timer, • remote access, • voice control, • The ability to set the default status of the device after a power failure, • µWiFi technology support	• Electric strike control - relay contact, • Multiple users support from anywhere, • Control many objects from one app, • remote access, • voice control, • door control input, • µWiFi technology support • Additional security option by logging in with username and password	• Control of the electric strike and automatic gate, • Multiple users support from anywhere, • Control many objects from one app, • remote access, • voice control, • µWiFi technology support • SMA-RP socket • µWiFi technology support	• Control of the electric strike and automatic gate, • Multiple users support from anywhere, • Control many objects from one app, • remote access, • voice control, • µWiFi technology support • Backup time : ~ 5 years	• Local control by physical button, • schedule, • timer, • remote access, • voice control, • µWiFi technology support	• Ultrasonic sensor, • Outputs : "Open Collector" (OC) type 250 mA, • Distance range of the virtual wall from the sensor : 2 ... 250 cm, • Operation modes (distances to virtual wall) : - Green : 140 cm (safe distance) - Blue : 48 ± 4 cm (obstacle close) - Red : 17 ± 3 cm (stop the vehicle) • Additional output for space occupancy signaling, • Small dimensions	• Multifunctional proximity sensor, • Distinguish between short and long signals, • remote access, • µWiFi technology support, • Possibility to hide the sensor, • Automatic calibration • LED indication	• Operation modes : - bistable, bistable + state memory, monostable NO, monostable NC, - Detection range : 3 cm - Trigger time : max. 8 s • Possibility to hide the sensor • Automatic calibration • LED indication	• Roller gate control in cooperation with security modules (photoeye, barrier, sensing edge), • Multiple users support from anywhere, • Control many objects from one app, • remote access, • voice control, • Keyboard built-in - 3 Touch control keys, • Backlit, touch control panel • SMA-RP socket • µWiFi technology support	• schedule, • timer, • sunrise and sunset mode, • remote access, • voice control, • µWiFi technology support	• Local control by physical button, • schedule, • timer, • sunrise and sunset mode, • remote access, • voice control, • µWiFi technology support	• Local control by physical button, • schedule, • timer, • sunrise and sunset mode, • remote access, • voice control, • µWiFi technology support	• Local control by physical button, • schedule, • timer, • sunrise and sunset mode, • remote access, • voice control, • µWiFi technology support	• Local control by physical button, • schedule, • timer, • sunrise and sunset mode, • remote access, • voice control, • µWiFi technology support	• Local control by physical button, • schedule, • timer, • sunrise and sunset mode, • remote access, • voice control, • µWiFi technology support	• Local control by physical button, • schedule, • timer, • sunrise and sunset mode, • remote access, • voice control, • µWiFi technology support	• Local control by physical button, • schedule, • timer, • sunrise and sunset mode, • remote access, • voice control, • µWiFi technology support	• Local control by physical button, • schedule, • timer, • sunrise and sunset mode, • remote access, • voice control, • µWiFi technology support	• Local control by physical button, • schedule, • timer, • sunrise and sunset mode, • remote access, • voice control, • µWiFi technology support	• Local control by physical button, • schedule, • timer, • sunrise and sunset mode, • remote access, • voice control, • µWiFi technology support	• Local control by physical button, • schedule, • timer, • sunrise and sunset mode, • remote access, • voice control, • µWiFi technology support	• Local control by physical button, • schedule, • timer, • sunrise and sunset mode, • remote access, • voice control, • µWiFi technology support	• Local control by physical button, • schedule, • timer, • sunrise and sunset mode, • remote access, • voice control, • µWiFi technology support
Housing	Plastic	Plastic	Plastic	Plastic	Plastic, Waterproof, Weatherproof	Plastic	Plastic	Self-extinguishing	Plastic	Plastic	Self-extinguishing, Surface-mounted (box)	Plastic	Plastic (ABS), DIN, TS-35 rail mounting	Plastic	Plastic (ABS), DIN, TS-35 rail mounting	Plastic	Plastic	Plastic (ABS), DIN, TS-35 rail mounting	Plastic	Self-extinguishing, Surface-mounted (box)	Plastic	Plastic (ABS)	Plastic (ABS)	Metal + Plastic (ABS)	
"Index of Protection"	IP20	IP20	IP20	IP20	IP54	IP20	IP20	IP20	IP20	IP20	IP44	IP20	IP20	IP20	IP20	IP20	IP20	IP20	IP44	IP20	IP20	IP20	IP20	IP20	
Color	Black	Black	Black	Black	Black	Black	Black	Black	Black	Black	White	Black	Black	Black	Black	Black	Black	Black	Black	Black	Black	Black	Black	Black	White
Operation temp	20 °C ... 50 °C	20 °C ... 50 °C	20 °C ... 50 °C	20 °C ... 50 °C	20 °C ... 50 °C	20 °C ... 50 °C	20 °C ... 50 °C	20 °C ... 50 °C	20 °C ... 50 °C	20 °C ... 50 °C	20 °C ... 50 °C	20 °C ... 50 °C	20 °C ... 50 °C	20 °C ... 50 °C	20 °C ... 50 °C	20 °C ... 50 °C	20 °C ... 50 °C	20 °C ... 50 °C	20 °C ... 50 °C	20 °C ... 50 °C	20 °C ... 50 °C	20 °C ... 50 °C	20 °C ... 50 °C	20 °C ... 50 °C	
Weight	0.024 kg	0.027 kg	0.04 kg	0.036 kg	0.1 kg	0.03 kg	0.027 kg	0.06 kg	0.026 kg	0.018 kg	0.37 kg	0.02 kg	0.062 kg	0.038 kg	0.04 kg	0.04 kg	0.024 kg	0.07 kg	0.027 kg	0.42 kg	0.04 kg	0.074 kg	0.028 kg	0.058 kg	
Dimensions	39 x 25 x 23 mm	35 x 33 x 23 mm	41 x 39 x 24 mm	39 x 39 x 22 mm	• 92 x 50 x 28 mm - without antenna • 230 x 85 x 28 mm - with antenna, vertical • 197 mm - Antenna	50 x 34 x 18 mm	35 x 33 x 23 mm	51 x 58 x 25 mm	53 x 40 x 18 mm	39 x 39 x 16 mm	• 129 x 96 x 57 mm - without antenna • 285 x 96 x 57 mm - with antenna, vertical • 197 mm - Antenna	38 x 33 x 20 mm	90 x 17.5 x 65 mm	42 x 39 x 22 mm	90 x 17.5 x 65 mm	41 x 39 x 23 mm	36 x 27 x 22 mm	90 x 17.5 x 65 mm	38 x 25 x 23 mm	• 129 x 96 x 57 mm - without antenna • 285 x 96 x 57 mm - with antenna, vertical • 197 mm - Antenna	38 x 35 x 23 mm	• 47 x 42 x 22 mm • Ø 6 x 30 mm - Probe • 1 m - Length of the cable (Probe)	148 x 46 x 16 mm	72 x 39 x 12 mm	72 x 39 x 12 mm
Manufacturer / Brand	BleBox	BleBox	BleBox	BleBox	BleBox	BleBox	BleBox	BleBox	BleBox	BleBox	BleBox	BleBox	BleBox	BleBox	BleBox	BleBox	BleBox	BleBox	BleBox	BleBox	BleBox	BleBox	BleBox	BleBox	
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00