






	ACOUSTIC GLASS BREAK DETECTOR AD800-AM ALARMTECH	ACOUSTIC GLASS BREAK DETECTOR DG-457 PARADOX	ACOUSTIC GLASS BREAK DETECTOR DS-PDBG8-EG2 Hikvision	ACOUSTIC GLASS BREAK DETECTOR INDIGO SATEL	ACOUSTIC GLASS BREAK DETECTOR MAGENTA SATEL
					
	774.21 PLN 774.21 PLN	99.00 PLN 99.00 PLN	120.00 PLN 120.00 PLN	96.00 PLN 96.00 PLN	88.00 PLN 88.00 PLN
Detection	Glass break detector	Glass break detector	Glass break detector	Glass break detector	Glass break detector
Detection angle	120 °
Range	9 m / 165 °	9 m - high level, 4.5 m - low level	max. 8 m	max. 6 m	max. 6 m
Sensitivity adjustment	—	✓	✓	✓	✓
Relay contacts rating (resistive load)	50 mA / 50 V DC	150 mA / 28 V DC	...	40 mA / 16 V DC	40 mA / 16 V DC
Alarm signaling	LED indicator, Signal to control panel	LED indicator, Signal to control panel	<ul style="list-style-type: none"> • LED diodes : <ul style="list-style-type: none"> - Red - high frequency trigger - Green - low frequency trigger - Blue - Alarm signaling, • Signal to control panel 	LED indicator, Signal to control panel	LED indicator, Signal to control panel
Alarm output	NC
Power supply	7 ... 30 V DC	9 ... 16 V DC / 35 mA	9 ... 16 V DC / 25 mA @ 12 V (max)	12 V DC / 12.5 mA	12 V DC / 10 mA
Current consumption	12 mA @ 12 V DC 7.3 mA @ 24 V DC
Environment class	I	...	II	II	II
Safety class	EN 50131-2-7-1:2013 Grade 3
"Index of Protection"	IP31
Housing	Plastic (ABS)
Main features	<ul style="list-style-type: none"> • detection of breaking plate, laminated or tempered glass - Glass thickness : max. 4 mm, laminated P2, P4 : 4 + 4 mm, Glass size max. 6 x 6 m • DRC - digital room acoustics compensation • Patented active "Anti-Masking" technology 	<ul style="list-style-type: none"> • detection of breaking plate, laminated or tempered glass • advanced dual-path microprocessor signal analysis • self test feature • Control panel BUS 	<ul style="list-style-type: none"> • detection of breaking plate, laminated or tempered glass • Glass thickness : 2.4 mm ... 6.4 mm • Glass size : 0.3 m x 0.3 m ... 3 m x 3 m • Digital detector • trimmer sensitivity adjustment • Tamper detection - opening the enclosure 	<ul style="list-style-type: none"> • detection of breaking plate, laminated or tempered glass • advanced dual-path microprocessor signal analysis • self test feature • trimmer sensitivity adjustment 	<ul style="list-style-type: none"> • detection of breaking plate, laminated or tempered glass • advanced dual-path microprocessor signal analysis • trimmer sensitivity adjustment
Color	White	White	White	White	White
Operation temp	5 °C ... 40 °C	-20 °C ... 50 °C	-10 °C ... 55 °C	-10 °C ... 55 °C	-10 °C ... 55 °C
Weight	0.1 kg	0.056 kg	0.05 kg	0.044 kg	0.04 kg
Dimensions	68 x 109 x 40 mm	66 x 90 x 25 mm	23 x 107 x 39 mm	48 x 78 x 23 mm	24 x 110 x 27 mm
Manufacturer / Brand	ALARMTECH	PARADOX	Hikvision	SATEL	SATEL
SAP Code	314300154
Guarantee	2 years	2 years	2 years	2 years	2 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00