

Code: INDIGO

## ACOUSTIC GLASS BREAK DETECTOR **INDIGO** SATEL

Net: **96.00 PLN** Gross: **96.00 PLN**

Sensor signals an alarm on registering a low-frequency tone (impact sound), followed by a high-frequency tone (sound of broken glass). The sensor starts to analyze a high-frequency channel after receiving the low-frequency sound wave, caused by the impact.

Detection by the microphone the impact sound wave is indicated by LED blink. If during this time the high-frequency tone (sound of broken glass) is detected, the detector will trigger an alarm.



### SPECIFICATION

Detection:	Glass break detector
Range:	max. 6 m
Environment class:	II
Sensitivity adjustment:	✓
Alarm signaling:	LED indicator, Signal to control panel
Relay contacts rating (resistive load):	40 mA / 16 V DC
Power supply:	12 V DC / 12.5 mA
Main features:	<ul style="list-style-type: none"><li>• detection of breaking plate, laminated or tempered glass</li><li>• advanced dual-path microprocessor signal analysis</li><li>• self test feature</li><li>• trimmer sensitivity adjustment</li></ul>
Color:	White
Operation temp:	-10 °C ... 55 °C
Weight:	0.044 kg
Dimensions:	48 x 78 x 23 mm
Manufacturer / Brand:	SATEL
Guarantee:	2 years

### PRESENTATION

Internal view of the housing:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60





**PACKAGE**

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

