

	CABLE CROSS-BNC/0.3M 0.3 m	CABLE CROSS-BNC/0.3MT 0.3 m	CABLE CROSS-BNC/0.3M- TP50 0.3 m	CABLE CROSS- BNC/0.3M*P50 0.3 m	CABLE CROSS-BNC/0.8M 0.8 m	CABLE CROSS-BNC/0.8M- TP10 0.8 m	CABLE CROSS- BNC/0.8M*P20 0.8 m	CABLE CROSS-BNC/1.5M 1.5 m	CABLE CROSS- BNC/1.5M*P20 1.5 m	CABLE CROSS-BNC/1.5MT 1.5 m	CABLE CROSS-BNC/1.5M- TP10 1.5 m	CABLE CROSS-BNC/3M 3 m	CABLE CROSS-BNC/3M*P10 3.0 m	CABLE CROSS-BNC/5M 5 m	CABLE CROSS-BNC/5M*P10 5.0 m	CABLE CROSS-BNC/10M 10.0 m	CABLE CROSS-COMBO/10M 10.0 m	CABLE CROSS-COMBO/20M 20 m	CABLE CROSS-COMBO/5M 5.0 m	CABLE LINK-BNC/1.5M 1.5 m	
	3.98 PLN 3.98 PLN	4.59 PLN 4.59 PLN	206.50 PLN 206.50 PLN	179.00 PLN 179.00 PLN	4.94 PLN 4.94 PLN	47.50 PLN 47.50 PLN	89.00 PLN 89.00 PLN	6.64 PLN 6.64 PLN	119.60 PLN 119.60 PLN	5.70 PLN 5.70 PLN	51.30 PLN 51.30 PLN	7.46 PLN 7.46 PLN	67.10 PLN 67.10 PLN	10.40 PLN 10.40 PLN	93.60 PLN 93.60 PLN	23.50 PLN 23.50 PLN	40.41 PLN 40.41 PLN	33.60 PLN 33.60 PLN	27.79 PLN 27.79 PLN	4.58 PLN 4.58 PLN	
In package	50 pcs The price for package	50 pcs The price for package	...	10 pcs The price for package	20 pcs The price for package	...	20 pcs The price for package	...	10 pcs The price for package	...	10 pcs The price for package	...	10 pcs The price for package	
Supported standards	AHD / HD-CVI / HD-TVI - 8.3 Mpx 4K UHD (max), PAL	...	PAL	...	
Cable	BNC plug / BNC plug	BNC plug / BNC plug	BNC plug / BNC plug	BNC plug / BNC plug	BNC Plug / BNC Plug	BNC plug / BNC plug	BNC Plug / BNC Plug	BNC plug / BNC plug	BNC Plug / BNC Plug	BNC plug / BNC plug	BNC plug / BNC plug	BNC Plug / BNC Plug	BNC Plug / BNC Plug	BNC Plug / BNC Plug	BNC Plug / BNC Plug	BNC Plug / BNC Plug	BNC plug / BNC plug	BNC plug / BNC socket	BNC plug / BNC socket	BNC Plug / BNC Socket	
Coaxial cable	
Power supply cable	
Impedance	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	
Length of the cable	0.3 m	0.3 m	0.3 m	0.3 m	0.8 m	0.8 m	0.8 m	1.5 m	1.5 m	1.5 m	1.5 m	3 m	3.0 m	5 m	5.0 m	10.0 m	10.0 m	20 m	5.0 m	1.5 m	
Main features	<ul style="list-style-type: none"> • Very easy and quick assembly • Very flexible, ideal for RACK cabinets usage 	<ul style="list-style-type: none"> • Highly flexible, with a sheath diameter of only 3 mm, ideal for RACK cabinets usage • Very easy and quick assembly 	<ul style="list-style-type: none"> • Highly flexible, with a sheath diameter of only 3 mm, ideal for RACK cabinets usage • Very easy and quick assembly 	<ul style="list-style-type: none"> • Very easy and quick assembly • Very flexible, ideal for RACK cabinets usage 	Very easy and quick assembly	<ul style="list-style-type: none"> • Highly flexible, with a sheath diameter of only 3 mm, ideal for RACK cabinets usage • Very easy and quick assembly 	Very easy and quick assembly	<ul style="list-style-type: none"> • Very easy and quick assembly • Very flexible, ideal for RACK cabinets usage 	<ul style="list-style-type: none"> • Very easy and quick assembly • Very flexible, ideal for RACK cabinets usage 	<ul style="list-style-type: none"> • Highly flexible, with a sheath diameter of only 3 mm, ideal for RACK cabinets usage • Very easy and quick assembly 	<ul style="list-style-type: none"> • Highly flexible, with a sheath diameter of only 3 mm, ideal for RACK cabinets usage • Very easy and quick assembly 	Very easy and quick assembly	<ul style="list-style-type: none"> • Very easy and quick assembly • Very flexible, ideal for RACK cabinets usage 	Very easy and quick assembly	<ul style="list-style-type: none"> • Very easy and quick assembly • Very flexible, ideal for RACK cabinets usage 	<ul style="list-style-type: none"> • Very easy and quick assembly • Very flexible, ideal for RACK cabinets usage 	<ul style="list-style-type: none"> • Very easy and quick assembly • Very flexible, ideal for RACK cabinets usage 	<ul style="list-style-type: none"> • Very easy and quick assembly • Corrosion resistance • Very flexible, ideal for small CCTV installations • Designed for cameras with current consumption below 450mA. At this current consumption, the power voltage for this length of the cable is lowered to 11V 	<ul style="list-style-type: none"> • Very easy and quick assembly • Corrosion resistance • Very flexible, ideal for small CCTV installations • Designed for cameras with current consumption below 150mA. At this current consumption, the power voltage for this length of the cable is lowered to 11V 	<ul style="list-style-type: none"> • Very easy and quick assembly • Corrosion resistance • Very flexible, ideal for small CCTV installations • Designed for cameras with current consumption below 900mA. At this current consumption, the power voltage for this length of the cable is lowered to 11V 	<ul style="list-style-type: none"> • Very easy and quick assembly • Very flexible
Weight	0.02 kg	0.02 kg	0.02 kg	0.02 kg	0.03 kg	0.03 kg	0.03 kg	0.06 kg	0.032 kg	0.04 kg	0.04 kg	0.110 kg	0.11 kg	0.09 kg	0.13 kg	0.160 kg	0.334 kg	0.4 kg	0.190 kg	0.040 kg	
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00