

Code: TR-1DL*P2

VIDEO BALUN TR-1DL*P2

Net: 12.27 PLN Gross: 12.27 PLN

The TR-1DL*P2 is designed to video signal transmission via twisted-pair cable. The device adapts the impedance of coaxial cable 75 Ω to the impedance of symmetrical line, ensuring transmission of video signal up to 250m @ 720p / 150m @ 1080p (twisted-pair cable category 5e) and eliminates asymmetric interferences.

It is important to pay attention to linking the adequate terminals: (+) and (-). Reverse connection would cause distortion of image.



SPECIFICATION

In package:	2 pcs The price for package
Standard:	• AHD - 8 Mpx 4K UHD, • HD-CVI - 8 Mpx 4K UHD, • HD-TVI - 8 Mpx 4K UHD, • CVBS - PAL, NTSC
Device type:	Passive
Number of channels:	1
Video transmission range:	• 250 m @ 720p - UTP cat. 5e • 150 m @ 1080p - UTP cat. 5e • 400 m @ CVBS - PAL, NTSC - UTP cat. 5e
Coaxial socket voltage range 75 Ω (CVBS):	1 Vpp
Attenuation:	• 4.43 MHz @ 0.31 dB • 11 MHz @ 0.49 dB • 21 MHz @ 0.75 dB • 38 MHz @ 1.07 dB • 42 MHz @ 1.08 dB • 67.5 MHz @ 1.41 dB The attenuation applies to two devices connected to each other
CMRR (dB @ 5MHz):	50 dB
Coaxial socket impedance:	75 Ω
Symmetrical socket impedance:	100 Ω
Coaxial socket type:	BNC Plug with cable
Symmetrical socket type:	Spring terminals
Operation temp:	-10 $^{\circ}$ C ... 55 $^{\circ}$ C
Permissible relative humidity:	< 95 %
Weight:	0.024 kg
Dimensions:	44 x 17 x 19 mm
Guarantee:	Lifetime warranty

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

PRESENTATION


Connecting the twisted-pair cable to the transformer:



Connectors:



Connection diagram:




- 1) Camera
 - 2) Monitor
 - 3) Twisted-pair cable (1 pair)
- Package:



OUR TESTS

Amplitude - frequency response - 2 transformers connected briefly (RF PWR OUT = 0 dBm):



OUR OPINIONS



- Tiny dimensions allow to easy montage of the transformers even in case of thick BNC sockets mounted.
- Spring terminals for twisted-pair cable allow to quick assembly without any tools.
- **Lifetime warranty.**

PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
 POL; 60-713 Poznań; Graniczna 10
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60