

Code: KT-609

RS-485 KEYBOARD CONTROLLER **KT-609**

Net: **416.00 PLN** Gross: **416.00 PLN**

Device enables quick access to the main functions, such as camera zoom and convenient 3D joystick control. Allows to control the most of camera models at direct mode (presets, routes, vectors control, etc.).



SPECIFICATION

Protocols:	Pelco-D, Pelco-P, DAHUA, HIK, SAMSUNG, KALATEL, KRE301, SONIC1, SONIC2, PIH717, RULE, SAE
Baud rates:	1200, 2400, 4800, 9600, 19200 bps
Cameras numbers (ID):	0 ... 255
Maximal control distance:	1200 m
Communication standard:	RS-485
Manipulator:	3-axis joystick, Speed proportional to the swing (possibility of zoom control by joystick)
Display:	LCD 16 characters
Main features:	• multiple protocols and different cameras speed supported on each channel • Speed Dome cameras, motor units, Motozoom cameras/lenses support • Admin password
Power supply:	12 V DC / 1 A (power adapter included)
Operation temp. / Relative humidity:	-10 °C ... 50 °C / max. 90 %
Weight:	0.71 kg
Dimensions:	305 x 150 x 105 mm
Guarantee:	2 years

PRESENTATION

Top view:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Keyboard connectors:



In the kit:



OUR OPINIONS



- User friendly and intuitive keyboard interface.
- LCD display with backlight.
- Modern and ergonomic design.

PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------