

Code: STH-10W-4K*P5

LED FLOODLIGHT **STH-10W-4K*P5** SonneTech

Net: **41.47 EUR** Gross: **41.47 EUR**

Illuminator can be used indoors and outdoors. Incomparably greater lifetime of the LEDs compared to traditional halogen bulb provides cheap and reliable operation. The use of multiple LEDs provides a better heat dissipation, and the longer lifetime of the reflector and allows for uniform light output.



SPECIFICATION

In package:	5 pcs The price for package
Luminous flux:	800 lm
Illumination angle:	120 °
Light color:	Neutral, 4000 ... 4500 K
Power supply:	110 V ... 240 V AC
Nominal power:	10 W 10.6 W (our tests result)
Power factor:	0.95
Power supply adapter efficiency:	84 %
Energy class:	A+
Illuminance in the distance of 3m:	52 lx
CRI:	> 70
Main features:	• LED SMD 5730 diodes • LED lifetime 35 000 h • Solid workmanship
Twilight switch:	—
Housing:	Aluminum
"Index of Protection":	IP65
Operation temp:	-20 °C ... 50 °C

Weight:	0.510 kg
Dimensions:	134 x 137 x 87 mm
Manufacturer / Brand:	SonneTech
Guarantee:	2 years

PRESENTATION

Front view:



Rear view:



OUR TESTS




DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
 POL; 60-713 Poznań; Graniczna 10
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Adding to offer a new line of LED products of the SonneTech company, we made tests of many floodlights available on the market. Below we present the principal advantages of our chosen floodlights:


Better heat dissipation through the well-finned rear panel:



The LED modules with SMD diodes better dissipate heat than COB diodes, by which is increased the lamp lifetime:



Between LED modules and housing is used a high quality thermal grease:



Glass pane better transmits light and does not yellow over time:



Precisely constructed and fitted housing and silicone seals, which do not deform and allow to resealing of the housing:




Mounting screws on the back of the housing beneficially affect the aesthetics of housing:



Well shaped reflector:




Safe and secure cable connections inside the housing:



The power cables with cross section $3 \times 0.75 \text{ mm}^2$:




Solid PE cable connection to the housing:



Power supply adapter is tightly flooded with a special thermal adhesive:



Thermography of floodlight test - respectively: LEDs, rear housing, power adapter:



OUR OPINIONS



- See our tests of floodlights that were made before we added them to offer.



-
- Very solid construction.

PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------