

Code: ZPP-4645F

## TV OVERVOLTAGE PROTECTOR **ZPP-4645F**

Net: 10.24 PLN Gross: 10.24 PLN

The ZPP-4645F is overvoltage protection of the receivers operating in terrestrial TV full band. It is used for example to protection of: TV receivers, HiFi sets, amplifiers. The device starts to work above 35 V voltage level, in 5-2400 MHz band at attenuation parameter below 0.5 dB. These parameters allow also to work in CATV with return channel applications. Replacement for MSS-01.



### SPECIFICATION

Frequency range:	5 ... 2400 MHz
Input, input connector:	F socket
Impedance:	75 $\Omega$
Attenuation:	< 0.5 dB
Voltage protection:	35 V
Residual voltage:	10 mV / 230 V AC
Screening efficiency:	5 ... 300 MHz - 85 dB 300 ... 470 MHz - 80 dB 470 ... 1000 MHz - 75 dB
Dimensions:	40 x 12.5 mm
Guarantee:	2 years

### PRESENTATION

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Connectors:



**PACKAGE**

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

