

Code: VD72P-2812/2

VANDALPROOF CAMERA **VD72P-2812/2** IR 700 TVL 2.8 ... 12 mm

Net: **264.23 PLN** Gross: **264.23 PLN**

Vandal-proof camera in metal housing with high resolution Sony Super HAD II sensor and wide range of view angle adjustment. It is equipped with IR illuminator, which is turned on by twilight sensor when illumination conditions are low.

Housing construction allows to mount the camera to the ceiling and the wall (image is right oriented in both cases). Camera module is mounted inside the dome housing, which allows to rotate the camera on any axis.

Camera Dome cover is protected by metal cable against falling during installation works. It is equipped with OSD menu controller, which allows to set and change the camera parameters without the need to remove or move the camera.

Camera is according to IP65 Index of Protection norm.



SPECIFICATION

Standard:	PAL
Sensor:	1/3 " Sony Super HAD II CCD
Digital Image Processor:	DSP Sony Effio-P
Resolution:	700 TVL
Lens:	2.8 ... 12 mm (adjusted by a screw driver, inside the housing)
View angle:	81 ° ... 23 ° (manufacturer data) 81 ° ... 28 ° (our tests result)
Range of IR illumination:	20 m
S/N ratio:	> 52 dB
Video output:	1 Vpp / 75 Ω
Power supply:	12 V / 360 mA
Main features:	• DNR - Digital Noise Reduction • WDR - Wide Dynamic Range • DIS - Digital Image Stabilization • BLC/HLC - Back Light / High Light Compensation • AGC Motion Detection • Privacy zones - max. 15 • Day/Night mode - configurable • EZOOM - Digital Zoom off • IR Optimizer IR illuminator optimization • Mirror - horizontal • Sharpness - sharper image outlines
OSD menu:	✓
Vandal-proof:	✓
Housing:	Metal
"Index of Protection":	IP65
Color:	White
Operation temp:	-10 °C ... 50 °C
Permissible relative humidity:	max. 95%
Weight:	0.75 kg

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Dimensions:	Ø 140 x 96 mm
Supported languages:	English, Chinese, Danish, French, Spanish, German, Polish, Portuguese, Russian, Turkish, Italian
Guarantee:	2 years

PRESENTATION

Camera view after remove the Dome cover:



Mounting side view:



In the kit:



OUR TESTS

Camera image at artificial illumination (about 30Lux):



Camera image at night conditions with internal built-in IR illuminator on:



Camera image at direct strong light opposite to camera:



OUR OPINIONS



- OSD controller placed on the cable much simplified the camera configuration.

PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

