

Code: VM-T101M

TOUCH SCREEN MONITOR VGA, HDMI, AUDIO **VM-T101M** 10.1 " VILUX

Net: **135.02 EUR** Gross: **135.02 EUR**

The VM-T101M professional CCTV monitor is equipped with a solid metal housing and a 10.1" capacitive touch screen with a resolution of 1280 x 800. The monitor is equipped with 2 mounting systems: mounting in the VESA standard and a set of frames enabling aesthetic, internal flush mounting of the screen in the housing of a larger device, advertising wall, interactive information terminal, etc.

The control keys are placed outside of monitor working area. This solution allows to place the monitor inside housing to protect it against change any settings by other people.

The device is designed to continuous work in closed spaces.

Attention! The touch function does not allow cooperation with recorders.



SPECIFICATION

Screen size:	10.1 "
Native resolution:	1280 x 800 px
Aspect ratios:	16 : 9
Matrix type:	TFT-LCD color matrix, LED backlight
Supported standards:	PAL/NTSC
Contrast:	1300 : 1
Brightness:	300 cd/m ²
Viewable angles:	175 ° horizontal 175 ° vertical
Response time:	5 ms
Speakers built-in:	✓
Signal connectors:	1x VGA 1x HDMI Audio: 1x Jack (for VGA) 1 x USB - touch screen
Housing type:	Metal
Monitor mounting standard:	VESA 75, VESA 100
Power supply:	12 V DC / 2.6 A (power adapter included)
Power consumption:	max. 31 W
Monitor control:	OSD - by monitor control keys

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Main features:	• capacitive touch screen, • The set includes a set of frames for aesthetic, internal flush mounting of the screen
Operation temp:	5 °C ... 40 °C
Weight:	1 kg
Dimensions:	260 x 177 x 36 mm
Supported languages:	English
Manufacturer / Brand:	VILUX
Guarantee:	2 years

PRESENTATION



Rear view:



Top view (control keys visible):



Monitor connectors:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------