COMPRESSION PLUG F/ZAC-TRISET-11/PCT

Net: 0.91 EUR Gross: 0.91 EUR

Precise thread eliminates problems with screwing the connectors on sockets. Double compression rings on the cable and the O-ring seal at connection side fully protect the cable and the installation equipment against water penetration.

Quick and easy assembly, as well as stability of operation of the equipment

are really worth the price.



SPECIFICATION

Connector type:	"F" Straight plug
Attachment of connector elements:	Compression mounting
Shield fastening:	Compression mounting
Wire mounting:	✓
Application:	Coaxial cable
Cable diameter:	max. 10.4 mm
Impedance:	75 Ω
Material:	Brass (Nickel-platted)
Watertightness:	✓
Example of application:	TRISET-11PE/ZEL
Main features:	Wide frequency range Watertightness of connector with cable connection Resistance to corrosion - made of non-ferrous metals and highest-quality dielectric Very low loss in the whole operating band Perfect matching to the transmission line within the whole operating band Properly compressed connection is highly resistant to break Many patent-pending solutions To crimp use the crimping tool, HT-5082R / HTL-548B
Weight:	0.002 kg
Dimensions:	Ø 13 mm x 47 mm
Guarantee:	2 years

PRESENTATION

2024-05-23 1/2



PACKAGE

Dimensions (L x W x H): 0x0x0 mm Gross Weight: 0 kg