

Code: BCS-SDIP1204-W

IP SPEED DOME CAMERA OUTDOOR **BCS-SDIP1204-W** - 1080p 2.7 ... 11 mm

Net: **193.31 EUR** Gross: **193.31 EUR**

IP camera equipped with very good high resolution sensor. Due to above it is perfect solution for surveillance systems requiring persons or vehicles recognition.

Very easy operation by Internet Explorer browser allows the users to convenient and remote support, and also remote management of the camera. Included camera software enables management and integrated monitoring of many network cameras.

For a few models of IP cameras working at $\geq 1920 \times 1080$ resolution we recommend to use of network with 1Gb/s bandwidth.



SPECIFICATION

Standard:	TCP/IP
Sensor:	1/2.7 " Progressive Scan CMOS
Matrix size:	2.0 Mpx
Resolution:	1920 x 1080 - 1080p 1280 x 720 - 720p 704 x 576 - D1
Scanning system:	Progressive
Lens:	2.7 ... 11 mm
View angle:	• 90 ° ... 27 ° (manufacturer data) • 110 ° ... 35 ° (our tests result)
Optical zoom:	x 4
Digital zoom:	x 16
Min. illumination:	0.05 Lux (color) 0.005 Lux (B/W)
S/N ratio:	> 50 dB (AGC off)
Preset rotation speed:	100 °/s
Rotation speed (manual control):	• 0.1 °/s ... 100 °/s (horizontal) • 0.1 °/s ... 60 °/s (vertical)
Horizontal rotation range:	355 °
Vertical rotation range:	0 ° ... 90 °
RS-485 interface:	—
Number of presets:	300

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Horizontal scan:	✓
Route settings:	5
Image compression method:	H.264 / MJPEG
Audio:	—
Bitrate:	• 448 ... 8192 kbps - H.264 • 56 ... 20480 kbps - MJPEG
Alarm inputs / outputs:	—
Main stream frame rate:	25 fps @ 1920 x 1080 Mpx
Network interface:	10/100 Base-T (RJ-45)
Network protocols:	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour
Memory card slot:	Micro SD memory cards up to 128GB support (possible local recording)
WEB Server:	Built-in, NVR compliance
Max. number of on-line users:	20
ONVIF:	2.4
Mobile phones support:	Port 37777 • Android: Free application DMSS • iOS (iPhone): Free application DMSS • Windows Phone: Free application wDMSS Lite There are also paid versions of mobile applications: gDMSS Plus, iDMSS Plus, wDMSS plus
Main features:	• ICR - Movable InfraRed filter • Motion Detection • 3D-DNR - Digital Noise Reduction • Configurable Privacy Zones • Sharpness - sharper image outlines • Mirror - Mirror image • AGC - Automatic Gain Control • Day/Night mode (color/b&w/auto)
Power supply:	• 12 V DC / 490 mA • PoE (802.3af)
Housing:	Speed Dome, Metal
Color:	White
Operation temp:	-30 °C ... 60 °C
"Index of Protection":	IP66
Weight:	0.522 kg
Dimensions:	Ø 122 x 89 mm
Manufacturer / Brand:	BCS
Guarantee:	2 years For products purchased after 01.01.2018, a 3-year warranty applies

PRESENTATION


Camera view after remove the Dome cover:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
 POL; 60-713 Poznań; Graniczna 10
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Camera image at direct strong light opposite to camera:



Camera image at night conditions with external IR illuminator on:



Camera image at night conditions, at different illumination values show below:

1 LUX:



0.1 LUX:



0.01 LUX:



0.001 LUX:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------