

Code: APT-200/IT

## REMOTE CONTROL **APT-200/IT** ABAX/ABAX2 SATEL

Net: **553.73 PLN** Gross: **553.73 PLN**

Universal remote controller to control the operation of ABAX/ABAX2 systems. In addition to arming and disarming the system, the keyfob provides other functions as well. For example, it can call for help (panic alarm) or control equipment connected to the system, like garage door, and so on.

Its additional advantage is the option to individually configure each button, so that its operation can better suit your needs.



### SPECIFICATION

|                                           |                                                                                                                                                                                                                                                                                                                                                                                   |
|-------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Support:                                  | ABAX/ABAX2                                                                                                                                                                                                                                                                                                                                                                        |
| Frequency band:                           | 868.0 MHz ... 868.6 MHz                                                                                                                                                                                                                                                                                                                                                           |
| Radio communication range (at open area): | max. 500 m @ ABAX<br>max. 2000 m @ ABAX2                                                                                                                                                                                                                                                                                                                                          |
| Battery:                                  | CR2032 3V (included)                                                                                                                                                                                                                                                                                                                                                              |
| Environmental class EN 50130-5:           | II                                                                                                                                                                                                                                                                                                                                                                                |
| Operation temp:                           | -10 °C ... 55 °C                                                                                                                                                                                                                                                                                                                                                                  |
| Permissible relative humidity:            | 93 ± 3 %                                                                                                                                                                                                                                                                                                                                                                          |
| Main features:                            | <ul style="list-style-type: none"><li>• LED indication</li><li>• five buttons whose operation can be individually defined in the system, allowing the keyfob functionality to be customized to the needs and habits of the user</li><li>• detection and signaling of low power of the keyfob battery</li><li>• attached snap hook-type handle for easy ordering of keys</li></ul> |
| Dimensions:                               | 38 x 78 x 16 mm                                                                                                                                                                                                                                                                                                                                                                   |
| Weight:                                   | 0.03 kg                                                                                                                                                                                                                                                                                                                                                                           |
| Manufacturer / Brand:                     | SATEL                                                                                                                                                                                                                                                                                                                                                                             |
| Guarantee:                                | 2 years                                                                                                                                                                                                                                                                                                                                                                           |

### PRESENTATION



In the kit:



## PACKAGE

|                                  |                    |
|----------------------------------|--------------------|
| Dimensions (L x W x H): 0x0x0 mm | Gross Weight: 0 kg |
|----------------------------------|--------------------|