

Code: APTI-N0401-S3

NVR **APTI-N0401-S3** 4 CHANNELS

Net: **158.40 PLN** Gross: **158.40 PLN**

The APTI-N0401-S3 digital recorder is a professional device applicable in surveillance systems. The H.264 video compression standard using to record video data, allows to get the best possible quality of recorded image at minimal network transfer and disk storage capacity. The menu options layout has been designed for all users, even beginners can easy navigate and change parameters in DVR settings without any problem.



SPECIFICATION

Standard:	TCP/IP
Supported resolutions:	4 @ 1920 x 1080 px, 4 @ 1280 x 960 px, 4 @ 1280 x 720 px
Video outputs:	1 pcs HDMI 1 pcs VGA
Audio support:	4 Channels - Audio from cameras
Audio inputs:	1 pcs CINCH
Audio outputs:	1 pcs CINCH
Image compression method:	H.264
Maximal total frame rate:	100 fps @ 1920 x 1080 px, 100 fps @ 1280 x 960 px, 100 fps @ 1280 x 720 px
Supported hard drives:	1 x 6 TB SATA
Recording modes:	Manual, Motion Detection, Schedule
Network protocols:	ONVIF, Private
External storage devices backup:	Records backup at (.avi) format to USB (pendrive)
Default admin user / password:	admin / 12345
Default IP address:	192.168.1.88
Web browser access ports:	80, 5000, 554
PC client access ports:	80, 5000, 554
Mobile client access ports:	80, 5000, 554
Searching and playback the records:	Records searching: timeline or file list. Playback: forward, fast Playback max. 1 camera in the same time
Bitrate:	28 Mbps
Network functions:	Network Client Software and IE browser: live view, playback and backup of the records, configuration of the recorder parameters
ONVIF:	✓

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Operation temp:	-10 °C ... 55 °C
Mobile phones support:	Port no.: 554 or access by a cloud (P2P) • Android: Free application FREEIP PRO , Android: Free application FREEIP • iOS (iPhone): Free application FREEIP PRO , iOS (iPhone): Free application FREEIP
Alarm inputs / outputs:	—
PTZ control:	IP Speed Dome Cameras
Motion Detection:	Split the screen into zones : 24 x 18 motion zones
Mouse support:	✓
IR remote controller in the set:	—
Power supply:	12 V DC / 2 A
Weight:	0.47 kg
Dimensions:	219 x 218 x 43 mm
Supported languages:	English, Arabic, Bulgarian, Chinese, Czech, French, Hebrew, Spanish, German, Polish, Portuguese, Russian, Thai, Turkish, Hungarian, Italian
Country of origin:	China
Manufacturer / Brand:	APTI
Guarantee:	2 years

PRESENTATION

Top view:



Rear panel:



In the kit:



Configuration and operation of the FreeIP cloud:
:

PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------