

Code: TC-R3110 SPEC:I/B/P8/L/S

NVR TC-R3110 SPEC:I/B/P8/L/S 10 CHANNELS, 8 PoE TIANDY

Net: 176.84 EUR Gross: 176.84 EUR

The product has been designed to minimize costs while maintaining high quality and ease of use. 8-port PoE Switch built-in.



SPECIFICATION

Standard:	IP
Supported resolutions:	max. 6 Mpx
Video outputs:	1 pcs HDMI 4K
Audio support:	Audio transmission via network - Audio from cameras
Audio inputs:	—
Audio outputs:	—
Image compression method:	S+265 / H.265 / S+264 / H.264
Supported hard drives:	1 x 6 TB SATA
Recording modes:	Manual, Motion Detection, Schedule
External storage devices backup:	Backup to USB drive (pendrive, external drive)
Searching and playback the records:	Records searching: by time and events type. Records playback: forward, backward, fast, slow Advanced searching (to the one second accuracy) 1/4 channel synchronous playback
Network interface:	1 x RJ-45 - 10 / 100 Mbps
Network functions:	Full support via network, Remote records copying, Web-Server built-in
ONVIF:	✓
Bitrate:	max. 60 Mbps
Default admin user / password:	admin / - The administrator password should be set at the first start

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Default IP address:	192.168.1.3
RTSP URL:	rtsp://user:password@192.168.1.3:554/1/1 - Main stream rtsp://user:password@192.168.1.3:554/1/2 - Sub stream
Web browser access ports:	80, 443, 3000, 3001, 3002, 23002
PC client access ports:	3000, 3001
Mobile client access ports:	3000, 3001
Mobile phones support:	Port no.: 3000 or access by a cloud (P2P) • Android: Free application EasyLive Plus • iOS (iPhone): Free application EasyLive Plus
Access from PC:	Port no.: 3000 or access by a cloud (P2P) - PC: Free application Easy7 Smart Client Express
Alarm inputs / outputs:	—
Motion Detection:	✓
Intelligent image analysis:	—
USB:	2 x USB 2.0
Mouse support:	✓
IR remote controller in the set:	—
Main features:	Support for Intelligent Image Analysis function, available in TIANDY cameras
Switch PoE:	8-port PoE Switch built-in, 30 W / Channel - PoE
Maximum total switch load:	70 W
Power supply:	48 V DC / 1.875 A (power adapter included)
Weight:	0.45 kg
Dimensions:	201 x 201 x 43 mm
Supported languages:	Polish, English, Spanish, Italian, Turkish, French, Dutch, Hebrew, German, Ukrainian, Portuguese
Manufacturer / Brand:	TIANDY
Guarantee:	3 years

PRESENTATION

Front panel:



Rear panel:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

