

Code: BCS-P-NVR3204-4K-II

NVR **BCS-P-NVR3204-4K-II** 32 CHANNELS BCS POINT

Net: **2 599.00 PLN** Gross: **2 599.00 PLN**

The BCS-P-NVR3204-4K-II digital recorder of the BCS POINT brand is a professional device used in IP surveillance systems.



SPECIFICATION

Standard:	TCP/IP
Supported resolutions:	max. 12 Mpx - 3000 x 4000 px
Video outputs:	1 pcs HDMI / VGA 1 pcs HDMI 4K
Audio support:	32 Channels - Audio from cameras
Audio inputs:	1 pcs CINCH - External microphone input
Audio outputs:	1 pcs CINCH
Image compression method:	H.265 / Ultra H.265 / H.264
Supported hard drives:	4 x 8 TB SATA
Recording modes:	Manual, Motion Detection, Schedule
Network protocols:	HTTP, HTTPS, TCP/IP, IPv4, UPnP, RTSP, RTP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, P2P
External storage devices backup:	Backup to USB drive (pendrive, external drive)
Searching and playback the records:	Records searching: by time and events type. Records playback: forward, backward, fast, slow Advanced searching (to the one second accuracy) All channels synchronous playback, Smart Search function
Bitrate:	max. 320 Mbps
Network functions:	Full support via network, Remote records copying, Web-Server built-in max. 128 on-line users
ONVIF:	2.4
USB:	2 pcs USB 2.0 1 pcs USB 3.0
Mobile phones support:	Port no.: 80 or access by a cloud (P2P) • Android: Free application BCS Point • iOS (iPhone): Free application BCS Point
Default IP address:	DHCP
Default admin user / password:	admin / 123456
Web browser access ports:	80, 554

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

PC client access ports:	80
Mobile client access ports:	80
Port ONVIF:	80
RTSP URL:	rtsp://192.168.1.66:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.66:554/unicast/c1/s1/live - Sub stream
Alarm inputs / outputs:	16 / 4
PTZ control:	<ul style="list-style-type: none"> • IP Speed Dome Cameras • RS-485 - PELCO-D/P
Motion Detection:	22 x 18 motion zones - after motion detection records detected channels only
Intelligent image analysis:	✓
Mouse support:	✓
IR remote controller in the set:	✓
Main features:	Fisheye-Dewarping - correction of the "fish eye" view to the perspective view
Power supply:	12 V DC / 5 A (power adapter included)
Weight:	3.26 kg
Dimensions:	440 x 350 x 46 mm
Supported languages:	English, German, Polish, Russian, Slovak
Country of origin:	China
Manufacturer / Brand:	BCS POINT
Guarantee:	3 years

PRESENTATION

Front panel:



Rear panel:



In the kit:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



OUR OPINIONS



- Audio transmission via network.

PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------