

Code: BNC-W/ZAC-RG-6/MSR

## COMPRESSION PLUG BNC-W/ZAC-RG-6/MSR

Net: 3.28 PLN Gross: 3.28 PLN

The connector is equipped with a plastic bush, which during compression of the connector is tightly pressed against the sheath of the cable (by putting on cone brass case - the compression ring). The BNC-W/ZAC-RG-6/MSR professional compression connector fulfills all recommendations of SCTE (The Society of Cable Telecommunications Engineers) for this kind connectors.

The features of the connector have been specially matched to the RG-6 cables. The dimensions are so matched that after compression connector is crimped on the cable sheath with a force so large that break the connector from the cable is impossible and so small that it does not damage the structure of the cable.



### SPECIFICATION

Connector type:	BNC Straight plug
Attachment of connector elements:	Compression mounting
Impedance:	75 Ω
Material:	Brass (Nickel-plated)
Application:	Coaxial cable
Wire mounting:	Pressing
Cable diameter:	max. 8.0 mm
Shield fastening:	Compression mounting
Watertightness:	✓
Example of application:	• RG6
Main features:	<ul style="list-style-type: none"><li>• Wide frequency range</li><li>• Very low loss in the whole operating band</li><li>• Watertightness of connector with cable connection</li><li>• Resistance to corrosion - made of non-ferrous metals and highest-quality dielectric</li><li>• Perfect matching to the transmission line within the whole operating band</li><li>• Properly compressed connection is highly resistant to break</li><li>• Many patent-pending solutions</li><li>• To crimp use the crimping tool HT-5082R</li></ul>
Weight:	0.015 kg
Dimensions:	Ø 14.5 mm x 37 mm
Guarantee:	2 years


### PRESENTATION

Connector view from cable assembly side:



## OUR TESTS

The manual of proper prepare the end of the cable and compress of the BNC connector:



:

## PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

