

	BROADBAND ANTENNA ASP-4	BROADBAND ANTENNA ASR-CLASSIC/P20	BROADBAND ANTENNA ASR-IO/GG	OMNIDIRECTIONAL ANTENNA MAGNET	OMNIDIRECTIONAL ANTENNA MEGA-CAMP	BROADBAND ANTENNA 28/5-12/21-60	LOGARITHMIC-PERIODIC ANTENNA ATK LOG/5-12/21-60 DIPOL	BROADBAND ANTENNA AK-GALAXY-COMBO	BROADBAND ANTENNA BX-1009-OLYMPIA RED EAGLE	DIRECTIONAL ANTENNA TX-W19-SILVER-COMBO TELMOR	DIRECTIONAL ANTENNA TX-W19-GOLD-COMBO TELMOR	BROADBAND ANTENNA ASP-8	UNIVERSAL ANTENNA DELTA-DU	BROADBAND ANTENNA DV-Z	ANTENNA DVB-T DVB-T SLIM	OMNIDIRECTIONAL ANTENNA KORONA	OMNIDIRECTIONAL ANTENNA COMPACT
																	
	11.23 EUR 11.23 EUR	53.02 EUR 53.02 EUR	65.04 EUR 65.04 EUR	25.49 EUR 25.49 EUR	27.19 EUR 27.19 EUR	35.58 EUR 35.58 EUR	27.32 EUR 27.32 EUR	11.80 EUR 11.80 EUR	25.96 EUR 25.96 EUR	24.30 EUR 24.30 EUR	33.14 EUR 33.14 EUR	18.52 EUR 18.52 EUR	22.28 EUR 22.28 EUR	12.27 EUR 12.27 EUR	22.20 EUR 22.20 EUR	21.90 EUR 21.90 EUR	14.92 EUR 14.92 EUR
Receiving channels	6 ... 60	6 ... 69	21 ... 48	• 6 ... 12, • 21 ... 49	• 6 ... 12, • 21 ... 48	• 5 ... 12, • 21 ... 48	• 5 ... 12, • 21 ... 60	• 6 ... 12, • 21 ... 60	• 6 ... 12, • 21 ... 60	• 6 ... 12, • 21 ... 48	• 6 ... 12, • 21 ... 48	6 ... 60	6 ... 12 21 ... 60	6 ... 12, 21 ... 60	• 6 ... 12, • 21 ... 69, • DAB	• 6 ... 12 • 21 ... 48	• 1 ... 12, • 21 ... 49
Gain	...	20 dB (max)	22 dB	30 ... 33 dB, 44 dB (max)	20 ... 33 dB, 44 dB (max)	...	...	...	...	...	...	...	...	...	20 dB (VHF) 30 ... 33 dB (UHF)	20 ... 30 dB	20 ... 30 dB
Gain	3.5 ... 10.5 dB	6 ... 14 dB	14 dBi	...	...	• 6 ... 7.4 dBi - VHF, • 6 ... 14.1 dBi - UHF	• 8 dBi - VHF, • 9 dBi - UHF	• 10 dB - VHF, • 12 dB - UHF	• 14 dB - VHF (manufacturer data), • 3 ... 6 dBi - VHF, • 9 ... 13 dBi - UHF	• 3 ... 6 dBi - VHF, • 9 ... 13 dBi - UHF	• 3 ... 7 dBi - VHF, • 9 ... 14 dBi - UHF	• 6.5 ... 9 dBi @ Channels 6 ... 12 • 10 ... 13.5 dBi @ Channels 21 ... 60	max. 28 dB	max. 28 dB	...	...	≤ 3 dB
Frequency range	...	...	470 ... 694 MHz	174 ... 230 MHz, 470 ... 696 MHz	• 174 ... 230 MHz, • 470 ... 696 MHz	...	...	...	...	• 174 ... 230 MHz • 470 ... 694 MHz	• 174 ... 230 MHz • 470 ... 694 MHz	...	...	...	174 ... 230 MHz 470 ... 862 MHz	...	...
Polarization	Horizontal	Horizontal	Horizontal	Horizontal	Horizontal	Horizontal / Vertical	Horizontal / Vertical	Horizontal / Vertical	Horizontal / Vertical	Horizontal / Vertical	Horizontal / Vertical	Horizontal	Vertical / Horizontal	Vertical / Horizontal	Horizontal / Vertical	Horizontal	Horizontal
Impedance	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω
Main features	• Number of elements : 10 • Matching transformer included	• Low Noise Ratio : 2.5 dB • Perfect reception of TV signals regardless of the distance from the transmitter • High resistance to wind and weather • It has very good parameters, due to use the high-quality low-noise amplifier • Very easy installation • Mast diameter : 25 ... 60 mm • Power supply : 5 ... 24 V / 30 mA (power adapter included)	• Low Noise Ratio • Perfect reception of TV signals regardless of the distance from the transmitter • Enhanced band-pass filter that eliminates interference generated by 5G/LTE/GSM signals • High resistance to wind and weather • Very easy installation • Mast diameter : 25 ... 60 mm • Power supply : 5 ... 12 V / 60 mA (power adapter included)	• Reception angle : 360 ° • Diode voltage indicator • High resistance to wind and weather • Very easy installation • Antenna cable + F plug, Antenna separator + IEC plug, Car lighter plug, Connecting cable TV - IEC, magnetic base - included	• Reception angle : 360 ° • Diode voltage indicator • High resistance to wind and weather • Very easy installation • Antenna cable + F plug, Antenna separator + IEC plug, Car lighter plug, Mast mounting diameter, U-Bolt - included • Mast diameter : max. 35 mm • DVB-T/T2 (VHF, UHF), DAB+	• The antenna has a built-in VHF/UHF multiplexer • The set includes impedance transformers • Number of elements : 28	• The antenna does not require a symmetrical balun, because it has output impedance matched to 75 Ω • Output - F socket	...	Built-in LTE filter	• Number of elements : 19 • DVB-T/T2, DAB+ compliance, • Built-in LTE / 5G filter • Operating in horizontal or vertical polarization in the VHF band • The antenna has a built-in VHF/UHF multiplexer • Built-in matching transformer • Possibility of connecting with one antenna cable or separate cables for each band • Weatherproof • Connector : F socket • The design of the antenna enables simple, quick assembly without the use of tools	• Number of elements : 25 • DVB-T/T2, DAB+ compliance, • Built-in LTE / 5G filter • Operating in horizontal or vertical polarization in the VHF band • The antenna has a built-in VHF/UHF multiplexer • Built-in matching transformers • Possibility of connecting with one antenna cable or separate cables for each band • Weatherproof • Connector : F socket • The design of the antenna enables simple, quick assembly without the use of tools	• It has a tight and UV-resistant housing • On the antenna body is placed a LED indicator informing about amplifier powering • It has very good parameters, due to use the high-quality low-noise amplifier • Antenna has also a special chip to minimize the current consumption • Power supply : 12 V / 100 mA (power adapter included) • Mast diameter : Ø max. 45 mm	• It has a tight and UV-resistant housing • It has very good parameters, due to use the high-quality low-noise amplifier • Small dimensions • Power supply : 12 V / 100 mA (power adapter included) • Mast diameter : Ø max. 35 mm	• Length of the cable : 4.0 m and 1.5 m • Flat construction • Diode voltage indicator • Antenna cable, Antenna separator + IEC plug, Power connector USB-A, Connecting cable TV - IEC, base for mounting the antenna, specialized bracket with a suction cup - included • Very easy installation	• Reception angle : 360 ° • Possibility to mount the antenna in many places, first of all on cars, yachts, campings • Small dimensions • Length of the cable : 5 m • Power supply : 12 ... 24 V / 30 mA	• Reception angle : 360 ° • Power supply : 12 V / 25 mA (power adapter included)	
Power supply	...	...	...	12 V / 24 V DC, 30 mA Car lighter plug	5 V DC, 30 mA USB-A plug	...	...	...	...	...	...	...	...	...	5 V DC / 30 mA from USB port	...	...
Weight	...	...	...	0.23 kg	0.28 kg	1.38 kg	0.6 kg	1.76 kg	1.76 kg	1.27 kg	1.55 kg	...	0.39 kg	...	0.221 kg	...	...
Dimensions	450 x 600 x 250 mm	820 x 455 x 220 mm	820 x 455 x 220 mm	Ø 280 x 80 mm	Ø 263 x 54 mm	1030 x 890 x 350 mm	725 x 913 x 40 mm	830 x 215 x 55 mm	1010 x 800 x 800 mm	921 x 740 x 530 mm	1160 x 860 x 540 mm	800 x 600 x 250 mm	355 x 210 x 50 mm	290 x 155 x 95 mm	• 220 x 125 x 17 mm (without bracket) • Ø 70 x 195 mm - Bracket	380 x 240 mm	260 x 55 mm
Manufacturer / Brand	TELMOR	TELMOR	TELMOR	WIEDYSKA	WIEDYSKA	DIPOL	DIPOL	RED EAGLE	TELMOR	TELMOR	TELMOR	TELMOR	TELMOR	WIEDYSKA	WIEDYSKA	WIEDYSKA	WIEDYSKA
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years