

Code: XD-2L

## MULTIPURPOSE WIRED DETECTOR **XD-2L** SATEL

Net: **48.07 CAD** Gross: **48.07 CAD**

The XD-2L wired detector can work in one of the 4 modes, which makes it an extremely universal device. Depending on your needs, the device can be configured as: magnetic detector, shock detector, shock detector with reed switch or water flood detector (FPX-1 external probe required - available separately).

The XD-2L works with any alarm control panel.



### SPECIFICATION

Support:	Alarm control panel
Detection:	Opening the door or window, Vibrations, Water
Environmental class EN 50130-5:	II
Protection class (Grade):	2
Sensitivity adjustment:	Applies to the shock detector
Alarm signaling:	LED indicator, Signal to control panel
Relay contacts rating (resistive load):	40 mA / 24 V DC
Power supply:	12 V DC / 15 mA (max)



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

Main features:	<ul style="list-style-type: none"> <li>• Operation modes : <ul style="list-style-type: none"> <li>- Magnetic detector</li> <li>- Opening the door or window</li> <li>- Maximum distance between detector and magnet : 15 mm (surface magnet), 19 mm (recessed magnet)</li> <li>- input for connecting a NC type wired detector</li> <li>- 1 Alarm output <ul style="list-style-type: none"> <li>- Shock detector</li> </ul> </li> <li>- Detection of shocks and vibrations associated with attempts to force a door or window</li> <li>- Range : 3 m</li> <li>- input for connecting a NC type wired detector</li> <li>- 1 Alarm output <ul style="list-style-type: none"> <li>- Shock and magnetic detector</li> </ul> </li> <li>- Detection of shocks and vibrations associated with attempts to force a door or window</li> <li>- Opening the door or window</li> <li>- input for connecting a NC type wired detector</li> <li>- 1 / 2 Alarm outputs <ul style="list-style-type: none"> <li>- Water flood detector - The required FPX-1 probe is available separately</li> </ul> </li> <li>- detecting the presence of water in spaces where there is a risk of leakage</li> <li>- 1 Alarm output</li> <li>• Alarm output : 2EOL/NC, NC</li> <li>• Built-in parametric resistors 2EOL: 2 x 1.1kΩ, 2 x 2.2 kΩ, 2 x 4.7 kΩ, 2 x 5.6 kΩ, 2 x 6.8 kΩ</li> <li>• LED indication - Remote configuration</li> <li>• Supply voltage control</li> <li>• Tamper detection - opening the enclosure</li> <li>• 2 magnets included (for surface and flush mounting)</li> <li>• Compliance with EN 50130-4, EN 50130-5, EN 50131-1, EN 50131-2-6 standards</li> </ul> </li> </ul>
Color:	White
Operation temp:	-10 °C ... 55 °C
Weight:	0.04 kg (detector)
Dimensions:	<ul style="list-style-type: none"> <li>• 25 x 136 x 29 mm (detector)</li> <li>• 15 x 52 x 6 mm (surface magnet)</li> <li>• Ø 10 x 28 mm (recessed magnet)</li> </ul>
Manufacturer / Brand:	SATEL
Guarantee:	2 years

## PRESENTATION

Front view:





Internal view of the housing:



Mounting side view:



In the kit:



#### PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

