

Code: DS-PDTPH-E-WE

WIRELESS TEMPERATURE DETECTOR AX PRO **DS-PDTPH-E-WE** Hikvision

Net: 73.04 EUR Gross: 73.04 EUR

The DS-PDTPH-E-WE temperature detector is used to measure temperature and humidity in a room. When using an external probe for measurement, only the temperature at the location of the probe is measured.

The DS-PDTPH-E-WE supports the other devices compatible with wireless HIKVISION AX PRO system.



SPECIFICATION

Support:	HIKVISION AX PRO
Detection:	Temperature / relative humidity
Temperature measurement range:	• -10 °C ... 55 °C (detector), • -35 °C ... 99 °C external (probe)
Alarm signaling:	• LCD display, • Signal to control panel
Frequency range:	868 MHz - Tri-X Wireless
Radio communication range (at open area):	max. 1200 m
Alarm inputs:	—
Power supply:	2 x battery LR3 (AAA) 1.5 V (included)
Backup time:	~ 2 years
Main features:	• LCD display - 2.7 " • Digital detector • Signal indicator • Battery charge indicator • Bidirectional communication • Compliance with the Tri-X protocol • AES-128 data encryption • Frequency hopping against jamming for reliable transmission • Tamper detection - opening the enclosure, removing from mounting surface • Remote configuration • Remote management • The device has the ability to work with the Hik-Connect application for mobile devices • Very easy installation

Color:	White
Operation temp:	-10 °C ... 55 °C
Permissible relative humidity:	10 % ... 90 % (non-condensing)
Weight:	0.074 kg
Dimensions:	• 63 x 63 x 18 mm • 3 m (cable length)
Manufacturer / Brand:	Hikvision
SAP Code:	314300162
Guarantee:	2 years

PRESENTATION

Front view:



Internal view of the housing:





Mounting side view:



Bottom view:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60