

Code: AGD-100-BR

WIRELESS GLASS BREAK DETECTOR **AGD-100-BR** SATEL

Net: **45.48 EUR** Gross: **45.48 EUR**

Sensor signals an alarm on registering a low-frequency tone (impact sound), followed by a high-frequency tone (sound of broken glass). The sensor starts to analyze a high-frequency channel after receiving the low-frequency sound wave, caused by the impact.

The AGD-100-BR supports the other devices compatible with wireless ABAX system.



SPECIFICATION

Detection:	detection of breaking plate, laminated or tempered glass
Support:	Satel ABAX
Alarm signaling:	Signal to control panel
Frequency band:	868 MHz ... 868.6 MHz
Radio communication range (at open area):	~ 500 m
Battery:	CR123A 3 V - 3.0 V (included)
Backup time:	~ 2 years
Main features:	• advanced dual-path microprocessor signal analysis • Remote configuration • Tamper protections
Operation temp:	-10 °C ... 55 °C
Color:	Brown
Weight:	0.03 kg
Dimensions:	26 x 112 x 28 mm
Manufacturer / Brand:	SATEL
Guarantee:	2 years

PRESENTATION


View after remove the cover:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Description of particular elements of the device:



1. microphone
2. tamper contact
3. Battery

Mounting side view:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------