

Code: SCD-120-12

BUFFERED POWER SUPPLY ADAPTER **SCD-120-12**

Net: **36.67 EUR** Gross: **36.67 EUR**

The buffered power supply adapter is designed to powering control panels, sensors, code locks, cameras, consoles, intercoms and other alarm system equipment.
Attention! If the power adaptor is using for continuous work (24H) the rated current of the adaptor should be less than 80% of the maximal current. Please pay attention for proper cooling conditions of the power adaptor during work!



SPECIFICATION

Adapter type:	Switching
Power voltage:	110 ... 240 V AC
Output voltage:	13.8 V DC
Output voltage adjustment:	11.6 ... 14.9 V
Maximal load:	10 A
Battery charging current:	0.5 A
Output power:	145 W
Efficiency:	84 %
Number of outputs:	1 pcs
Protections:	• Overvoltage • Overload protection • Short-circuit
Operation temp. / Relative humidity:	-10 °C ... 60 °C / 20 % ... 90 %
Weight:	0.545 kg
Dimensions:	162 x 99 x 44 mm
Guarantee:	2 years

PRESENTATION

Adapter connectors:



Live wire (230V)
 Neutral wire
 Grounding
 DC "-" output
 DC "+" output
 A+ Not connected
 B- (+) battery output
 B+ (-) battery output
 ADJ - Output voltage adjustment

OUR OPINIONS



- Switching time: 1.5 s - it is not suitable for IP, Access Control, Intruder Alarms systems and for recorders powering.

PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------