

Code: AXON-MINI/TELECOM

## OVERVOLTAGE LIMITER **AXON-MINI/TELECOM** (1 + 2 OUTLETS) +TEL

Net: 7.26 EUR Gross: 7.26 EUR

The AXON-MINI/TELECOM ensures continuous protection against overvoltages of three devices and ADSL transmission line. It is equipped with one grounded power outlet, two flat non-grounded power outlets and two RJ-11 phone sockets. It is perfect solution to increase the functionality of the single surface power outlet.



### SPECIFICATION

|                                                   |                                                                 |
|---------------------------------------------------|-----------------------------------------------------------------|
| Rated voltage:                                    | 230 V AC / 50 Hz                                                |
| Total maximal current:                            | 10 A                                                            |
| Nominal discharge current for TEL line:           | 2 kA (La,b/PE) - (8/20µs)                                       |
| Maximal total load:                               | 2300 W                                                          |
| Response time:                                    | < 25 ns                                                         |
| Number of outlets:                                | 3 outlets, two-contact 10A/250V including 1 with ground contact |
| TEL line maximal stroke current:                  | 5 kA (La,b/PE) - (8/20µs)                                       |
| Leak current:                                     | < 0.5 mA                                                        |
| Nominal voltage of surge suppressor:              | 250 V / 50 Hz                                                   |
| Protection level of surge suppressor:             | ≤ 1.3 kV (L/N)                                                  |
| Nominal stroke current:                           | 2 kA (L/N) - (8/20µs)                                           |
| ADSL TELEPHONE LINE:                              |                                                                 |
| Phone sockets type:                               | RJ11 (6P4C)                                                     |
| Protected wires of ADSL line:                     | 2 z 4                                                           |
| Maximum stroke current:                           | 6.5 kA (L/N) - (8/20µs)                                         |
| Rise time of surge suppressor for TEL line:       | ≤ 25 ns                                                         |
| Nominal voltage of surge suppressor for TEL line: | 150 V                                                           |
| Level of surge protection for TEL line:           | ≤ 1 kV (La,b/PE)                                                |
| Electric shock protection system:                 | Ground connectors (pins) connected with ground wire of AC mains |
| Housing:                                          | Plastic - non-flammable                                         |
| Dimensions:                                       | 131 x 55 x 75 mm                                                |

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

|            |         |
|------------|---------|
| Weight:    | 0.13 kg |
| Guarantee: | 2 years |

## PRESENTATION

In the kit:



Package:



## PACKAGE

|                                  |                    |
|----------------------------------|--------------------|
| Dimensions (L x W x H): 0x0x0 mm | Gross Weight: 0 kg |
|----------------------------------|--------------------|