

	POWER DISTRIBUTION UNIT L196VP	POWER DISTRIBUTION UNIT PD-6-F/RACK	POWER DISTRIBUTION UNIT L197F	POWER DISTRIBUTION UNIT PD-6R	POWER DISTRIBUTION UNIT PD-6R3P 1.8 m	POWER DISTRIBUTION UNIT PD-6R-2P 1.8 m	POWER DISTRIBUTION UNIT PD-6-R/OP	POWER DISTRIBUTION UNIT PD-6R-SPD-1P	POWER DISTRIBUTION UNIT PD-6R-SPD-3L	POWER DISTRIBUTION UNIT PD-6-R/USB	POWER DISTRIBUTION UNIT PD-6R/VA	POWER DISTRIBUTION UNIT PD-7/RACK	POWER DISTRIBUTION UNIT PD-8R	POWER DISTRIBUTION UNIT PD-8R/IEC 1.8 m	POWER DISTRIBUTION UNIT PD-8R/IEC-N 1.8 m	POWER DISTRIBUTION UNIT PD-9R	POWER DISTRIBUTION UNIT PD-9R/IEC 1.8 m	POWER DISTRIBUTION UNIT L198	POWER DISTRIBUTION UNIT PD-7R-N 1.8 m	POWER DISTRIBUTION UNIT PD-8/RACK-N	POWER DISTRIBUTION UNIT PD-4R14	POWER DISTRIBUTION UNIT PD-4-R10R 1.8 m	POWER DISTRIBUTION UNIT PD-7/RACK/IEC	POWER DISTRIBUTION UNIT PD-8/RACK	POWER DISTRIBUTION UNIT PD-8/RACK/IEC	POWER DISTRIBUTION UNIT PD-7K/RACK	POWER DISTRIBUTION UNIT PD-8K/RACK	POWER DISTRIBUTION UNIT ACAR-E5/FA/RACK	POWER DISTRIBUTION UNIT ACAR-S8/FA/RACK	POWER DISTRIBUTION UNIT PD-9RACK		
Rated voltage	19.50 EUR 230 V AC / 50 Hz	16.55 EUR 230 V AC / 50 Hz	22.17 EUR 230 V AC / 50 Hz	16.06 EUR 230 V AC / 50 Hz	18.73 EUR 230 V AC / 50 Hz	22.55 EUR 230 V AC / 50 Hz	17.58 EUR 230 V AC / 50 Hz	18.73 EUR 230 V AC / 50 Hz	21.41 EUR 230 V AC / 50 Hz	24.85 EUR 230 V AC / 50 Hz	49.31 EUR 230 V AC / 50 Hz	17.55 EUR 230 V AC / 50 Hz	17.58 EUR 230 V AC / 50 Hz	17.58 EUR 230 V AC / 50 Hz	20.64 EUR 230 V AC / 50 Hz	17.20 EUR 230 V AC / 50 Hz	17.97 EUR 230 V AC / 50 Hz	20.64 EUR 230 V AC / 50 Hz	19.09 EUR 230 V AC / 50 Hz	16.82 EUR 230 V AC / 50 Hz	14.32 EUR 230 V AC / 50 Hz	15.29 EUR 230 V AC / 50 Hz	18.83 EUR 230 V AC / 50 Hz	22.79 EUR 230 V AC / 50 Hz	20.45 EUR 230 V AC / 50 Hz	19.88 EUR 230 V AC / 50 Hz	22.27 EUR 230 V AC / 50 Hz	26.93 EUR 230 V AC / 50 Hz	29.27 EUR 230 V AC / 50 Hz	28.51 EUR 230 V AC / 50 Hz		
Total maximal current	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	
Maximal total load	3500 W	3680 W	3500 W	3680 W	3680 W	3680 W	3680 W	3680 W	3680 W	3680 W	3680 W	3680 W	3680 W	3680 W	2500 W	3680 W	3680 W	3500 W	4000 W	4000 W	3500 W	3500 W	3680 W	3680 W	3680 W	3680 W	3680 W	3680 W	3680 W	3680 W		
Assembly	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets		
Number of outlets	6 for universal plug 230 V (Schuko)	6 for universal plug 230 V (DIN 49441)	7 for universal plug 230 V (Schuko)	6 x CEE 7/5	6 x CEE 7/5	6 x CEE 7/5	6 x CEE 7/5	6 x CEE 7/5	6 x CEE 7/5	6 x CEE 7/5	6 x CEE 7/5	7 x CEE 7/5	8 x CEE 7/5	8 x CEE 7/5	8 x CEE 7/5	9 x CEE 7/5	9 x CEE 7/5	8 for universal plug 230 V (Schuko)	7 x CEE 7/5	8 for universal plug 230 V (Schuko)	4 x CEE 7/5	4 x CEE 7/5	7 x CEE 7/5	8 for universal plug 230 V (DIN 49441)	8 for universal plug 230 V (DIN 49441)	7 x CEE 7/5	8 for universal plug 230 V (DIN 49441)	5 grounded outlets 10A/250V	8 grounded outlets 10A/250V	9 for universal plug 230 V (DIN 49441)		
Length of the power cable	1.8 m	2.15 m	1.8 m	1.8 m cable with power connector CEE 7/7	1.8 m cable with power connector CEE 7/7	1.8 m cable with power connector CEE 7/7	1.8 m cable with power connector CEE 7/7	1.8 m cable with power connector CEE 7/7	1.8 m cable with power connector CEE 7/7	1.8 m cable with power connector CEE 7/7	1.8 m cable with power connector CEE 7/7	2 m	1.8 m cable with power connector CEE 7/7	1.8 m - cable with power connector IEC320 C14	1.8 m - cable with power connector IEC320 C14	1.8 m cable with power connector CEE 7/7	1.8 m - cable with power connector IEC320 C14	1.8 m	1.8 m cable with power connector CEE 7/7	1.8 m	1.8 m	1.8 m	2 m - cable with power connector IEC320 C14	2 m	2 m	2 m	2 m	2 m	2 m	2 m	3 m	
Nominal voltage of surge suppressor	250 V / 50 Hz	250 V / 50 Hz	250 V / 50 Hz	250 V / 50 Hz	250 V / 50 Hz	250 V / 50 Hz	250 V / 50 Hz	250 V / 50 Hz	250 V / 50 Hz	250 V / 50 Hz	250 V / 50 Hz	250 V / 50 Hz	250 V / 50 Hz	250 V / 50 Hz	250 V / 50 Hz	250 V / 50 Hz	250 V / 50 Hz	250 V / 50 Hz	250 V / 50 Hz	250 V / 50 Hz	250 V / 50 Hz	250 V / 50 Hz	250 V / 50 Hz	250 V / 50 Hz	250 V / 50 Hz	250 V / 50 Hz	250 V / 50 Hz	250 V / 50 Hz	250 V / 50 Hz	250 V / 50 Hz		
Automatic delayed fuse	10 A / 250 V	10 A / 250 V	10 A / 250 V	10 A / 250 V	10 A / 250 V	10 A / 250 V	10 A / 250 V	10 A / 250 V	10 A / 250 V	10 A / 250 V	10 A / 250 V	10 A / 250 V	10 A / 250 V	10 A / 250 V	10 A / 250 V	10 A / 250 V	10 A / 250 V	10 A / 250 V	10 A / 250 V	10 A / 250 V	10 A / 250 V	10 A / 250 V	10 A / 250 V	10 A / 250 V	10 A / 250 V	10 A / 250 V	10 A / 250 V	10 A / 250 V	10 A / 250 V	10 A / 250 V	10 A / 250 V	
Protection level of surge suppressor	± 1.3 kV (L/N)	± 1.3 kV (L/N)	± 1.3 kV (L/N)	± 1.3 kV (L/N)	± 1.3 kV (L/N)	± 1.3 kV (L/N)	± 1.3 kV (L/N)	± 1.3 kV (L/N)	± 1.3 kV (L/N)	± 1.3 kV (L/N)	± 1.3 kV (L/N)	± 1.3 kV (L/N)	± 1.3 kV (L/N)	± 1.3 kV (L/N)	± 1.3 kV (L/N)	± 1.3 kV (L/N)	± 1.3 kV (L/N)	± 1.3 kV (L/N)	± 1.3 kV (L/N)	± 1.3 kV (L/N)	± 1.3 kV (L/N)	± 1.3 kV (L/N)	± 1.3 kV (L/N)	± 1.3 kV (L/N)	± 1.3 kV (L/N)	± 1.3 kV (L/N)	± 1.3 kV (L/N)	± 1.3 kV (L/N)	± 1.3 kV (L/N)	± 1.3 kV (L/N)	± 1.3 kV (L/N)	
Housing type	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	
Nominal stroke current	2 kA (L/N) - 8/20 µs	2 kA (L/N) - 8/20 µs	2 kA (L/N) - 8/20 µs	2 kA (L/N) - 8/20 µs	2 kA (L/N) - 8/20 µs	2 kA (L/N) - 8/20 µs	2 kA (L/N) - 8/20 µs	2 kA (L/N) - 8/20 µs	2 kA (L/N) - 8/20 µs	2 kA (L/N) - 8/20 µs	2 kA (L/N) - 8/20 µs	2 kA (L/N) - 8/20 µs	2 kA (L/N) - 8/20 µs	2 kA (L/N) - 8/20 µs	2 kA (L/N) - 8/20 µs	2 kA (L/N) - 8/20 µs	2 kA (L/N) - 8/20 µs	2 kA (L/N) - 8/20 µs	2 kA (L/N) - 8/20 µs	2 kA (L/N) - 8/20 µs	2 kA (L/N) - 8/20 µs	2 kA (L/N) - 8/20 µs	2 kA (L/N) - 8/20 µs	2 kA (L/N) - 8/20 µs	2 kA (L/N) - 8/20 µs	2 kA (L/N) - 8/20 µs	2 kA (L/N) - 8/20 µs	2 kA (L/N) - 8/20 µs	2 kA (L/N) - 8/20 µs	2 kA (L/N) - 8/20 µs	2 kA (L/N) - 8/20 µs	
Leak current	< 0.5 mA	< 0.5 mA	< 0.5 mA	< 0.5 mA	< 0.5 mA	< 0.5 mA	< 0.5 mA	< 0.5 mA	< 0.5 mA	< 0.5 mA	< 0.5 mA	< 0.5 mA	< 0.5 mA	< 0.5 mA	< 0.5 mA	< 0.5 mA	< 0.5 mA	< 0.5 mA	< 0.5 mA	< 0.5 mA	< 0.5 mA	< 0.5 mA	< 0.5 mA	< 0.5 mA	< 0.5 mA	< 0.5 mA	< 0.5 mA	< 0.5 mA	< 0.5 mA	< 0.5 mA	< 0.5 mA	
Maximum stroke current	10 kA (L/N) - 8/20 µs 2 type	10 kA (L/N) - 8/20 µs 2 type	10 kA (L/N) - 8/20 µs 2 type	10 kA (L/N) - 8/20 µs 2 type	10 kA (L/N) - 8/20 µs 2 type	10 kA (L/N) - 8/20 µs 2 type	10 kA (L/N) - 8/20 µs 2 type	10 kA (L/N) - 8/20 µs 2 type	10 kA (L/N) - 8/20 µs 2 type	10 kA (L/N) - 8/20 µs 2 type	10 kA (L/N) - 8/20 µs 2 type	10 kA (L/N) - 8/20 µs 2 type	10 kA (L/N) - 8/20 µs 2 type	10 kA (L/N) - 8/20 µs 2 type	10 kA (L/N) - 8/20 µs 2 type	10 kA (L/N) - 8/20 µs 2 type	10 kA (L/N) - 8/20 µs 2 type	10 kA (L/N) - 8/20 µs 2 type	10 kA (L/N) - 8/20 µs 2 type	10 kA (L/N) - 8/20 µs 2 type	10 kA (L/N) - 8/20 µs 2 type	10 kA (L/N) - 8/20 µs 2 type	10 kA (L/N) - 8/20 µs 2 type	10 kA (L/N) - 8/20 µs 2 type	10 kA (L/N) - 8/20 µs 2 type	10 kA (L/N) - 8/20 µs 2 type	10 kA (L/N) - 8/20 µs 2 type	10 kA (L/N) - 8/20 µs 2 type	10 kA (L/N) - 8/20 µs 2 type	10 kA (L/N) - 8/20 µs 2 type	10 kA (L/N) - 8/20 µs 2 type	
Response time	< 25 ns	< 25 ns	< 25 ns	< 25 ns	< 25 ns	< 25 ns	< 25 ns	< 25 ns	< 25 ns	< 25 ns	< 25 ns	< 25 ns	< 25 ns	< 25 ns	< 25 ns	< 25 ns	< 25 ns	< 25 ns	< 25 ns	< 25 ns	< 25 ns	< 25 ns	< 25 ns	< 25 ns	< 25 ns	< 25 ns	< 25 ns	< 25 ns	< 25 ns	< 25 ns	< 25 ns	
Switch	Yes (with built-in LED indicator)	two-way, with light indication	Yes (with built-in LED indicator)	two-way, with light indication	...	two-way, with light indication	two-way, with light indication	two-way, with light indication	two-way, with light indication	two-way, with light indication	two-way, with light indication	two-way, with light indication	two-way, with light indication	two-way, with light indication	two-way, with light indication	two-way, with light indication	two-way, with light indication	Yes (with built-in LED indicator)	Yes (with built-in LED indicator and protected by a cover)	Yes (with built-in LED indicator and protected by a cover)	Yes (with built-in LED indicator)	Yes (with built-in LED indicator)	Yes (with built-in LED indicator)	Yes (with built-in LED indicator)	Yes (with built-in LED indicator)	Yes (with built-in LED indicator)	Yes (with built-in LED indicator)	Yes (with built-in LED indicator)	Yes (with built-in LED indicator)	Yes (with built-in LED indicator)	Yes (with built-in LED indicator)	
Main features	• Overvoltage protection • LED indicators displaying the device's operating status	...	Overload protection	...	Circuit Breaker : 16 A, C type, 1P	Circuit Breaker, 16 A, C type, 2P	Overvoltage protection - Switch disconnector with fuse	• Overvoltage protection	• Signaling a lack of grounding • Overvoltage protection • AC input voltage presence indication	2 x USB socket : 5 V / 3 A	• Supply voltage measurement, • Supply current measurement	Yes (with built-in LED indicator)	Yes (with built-in LED indicator and protected by a cover)	Yes (with built-in LED indicator and protected by a cover)	Yes (with built-in LED indicator)	Yes (with built-in LED indicator)	Yes (with built-in LED indicator)	Yes (with built-in LED indicator)	Yes (with built-in LED indicator)	Yes (with built-in LED indicator)	Yes (with built-in LED indicator)	Yes (with built-in LED indicator)	Yes (with built-in LED indicator)	Yes (with built-in LED indicator)	Yes (with built-in LED indicator)
Housing
Weight	0.75 kg	0.830 kg	0.8 kg	0.74 kg	0.83 kg	0.91 kg	0.76 kg	0.76 kg	0.76 kg	0.76 kg	0.76 kg	0.72 kg	0.78 kg	0.75 kg	0.75 kg	0.77 kg	0.75 kg	0.74 kg	0.74 kg	0.72 kg	0.510 kg	0.52 kg	0.69 kg	0.830 kg	0.700 kg	0.35 kg	0.830 kg	0.93 kg	0.61 kg	0.85 kg		
Dimensions	482 x 45 x 54 mm	530 x 75 x 55 mm	484 x 45 x 56 mm	483 x 45 x 50 mm	483 x 44 x 84 mm	483 x 45 x 85 mm	483 x 45 x 54 mm	483 x 44 x 54 mm	483 x 45 x 54 mm	483 x 45 x 55 mm	483 x 45 x 54 mm	483 x 45 x 54 mm	483 x 44 x 54 mm	483 x 45 x 54 mm	481 x 45 x 45 mm	483 x 44 x 54 mm	483 x 45 x 44 mm	484 x 45 x 57 mm	480 x 45 x 51 mm	484 x 46 x 51 mm	257 x 45 x 45 mm	257 x 45 x 50 mm	482 x 46 x 44 mm	530 x 75 x 55 mm	482 x 46 x 44 mm	450 x 45 x 44 mm	450 x 45 x 44 mm	484 x 54 x 55 mm	445 x 54 x 55 mm	448 x 45 x 45 mm		
Length of the cable
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00