

HD-CVI, PAL, TCP/IP DVR BCS-CVR04022M-III 4 CHANNELSNet: **2 045.41 DKK** Gross: **2 045.41 DKK**

Tribrid DVR working in three standards: HD-CVI, IP and analog.

The HD-CVI interface allows to transmission of analog, composite video signal via coaxial cable. It enables the transmission of HD resolution images for even 500 m distance with keeping the low costs of the installation. During transmission there are no delays and is maintained the original, high quality image.

**SPECIFICATION**

Standard:	HD-CVI, PAL, TCP/IP
Maximal total frame rate:	• HD-CVI, PAL : 100 fps @ 1920 x 1080 px, 100 fps @ 1280 x 720 px, 100 fps @ 960 x 576 px, 100 fps @ 704 x 576 px • IP : 50 fps @ max. 1080p
Recording speed adjustment:	• HD-CVI, PAL 1 ... 25 fps @ 1920 x 1080 1 ... 25 fps @ 1280 x 720 1 ... 25 fps @ 960 x 576 1 ... 25 fps @ 704 x 576 for each channel • IP 1 ... 25 fps @ max. 1920 x 1080 for each channel
Operation modes:	• 4 x HD-CVI / PAL • 3 x HD-CVI / PAL + 1 x IP max. 1080p • 2 x HD-CVI / PAL + 2 x IP max. 1080p
Video inputs:	4 pcs BNC, HD-CVI / PAL
Video outputs:	1 pcs HDMI 1 pcs VGA
Audio inputs:	4 pcs BNC 1 pcs BNC - Microphone
Audio outputs:	1 pcs BNC 1 pcs BNC - Microphone
Image compression method:	H.264
Number of compression levels:	6
Image records resolutions:	1920 x 1080 1280 x 720 960 x 576 704 x 576
Recording modes:	Manual, Sensor, Motion detection, Schedule
Supported hard drives:	max. 2 x 8 TB SATA

External storage devices backup:	Save single frames and whole records from DVR drive to the USB drive
Searching and playback the records:	Records searching: by time + timeline with record type. Playback: forward, fast, slow, step Advanced searching (to the one second accuracy)
Network functions:	Network Client Software and IE browser: live view, playback and backup of the records, partial configuration of the recorder parameters
Network protocols:	HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP
Mobile phones support:	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS
Alarm inputs / outputs:	4 / 3
PTZ control:	IP Speed Dome Cameras - Control compatible with coax PTZ HD-CVI RS-485 PELCO-D/P
Motion Detection:	Split the screen into zones 22 x 18 motion zones Very good sensitivity after motion detection records detected channels only
Mouse support:	✓
IR remote controller in the set:	—
Power supply:	12 V DC / 3 A
Weight:	1.75 kg
Dimensions:	375 x 287 x 53 mm
Supported languages:	English, Polish
Country of origin:	China
Manufacturer / Brand:	BCS
Guarantee:	2 years For products purchased after 01.01.2018, a 3-year warranty applies

PRESENTATION

Front view:



Rear view:



In the kit:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

