

Code: PSBSH-2012B

BUFFERED SWITCHING POWER SUPPLY ADAPTER **PSBSH-2012B**

Net: **348.00 PLN** Gross: **348.00 PLN**

The buffered power supply adapter is designed to powering control panels, sensors, code locks, cameras, consoles, intercoms and other alarm system equipment.
Attention! If the power adaptor is using for continuous work (24H) the rated current of the adaptor should be less than 80% of the maximal current.



SPECIFICATION

Adapter type:	Switching
Input voltage:	230 V AC
Output voltage:	• 11 ... 13.8 V DC (mains mode) • 10 ... 13.8 V DC (battery mode)
Max. output current (total):	2 A
Power:	30 W
Battery charging current:	0.2 A / 0.5 A
Protections:	• Short-circuit • Reverse polarity connection • Overload • Overvoltage • Discharge • Overheat • Tamper
Adapter operation control:	• AC input voltage presence indication • Battery charging indication • DC output voltage presence indication
Place for battery:	12V/7Ah
Max. battery dimensions:	155 x 100 x 70 mm
Housing type:	Plastic (ABS), hermetic
"Index of Protection":	IP65
Weight:	2.2 kg
Dimensions:	265 x 185 x 95 mm
Manufacturer / Brand:	PULSAR

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Guarantee:	2 years
------------	---------

PRESENTATION

Front view:



Wall mounting side view:



In the kit:

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

