

Code: PSBS-3012C

BUFFERED SWITCHING POWER SUPPLY ADAPTER **PSBS-3012C**

Net: **96.77 EUR** Gross: **96.77 EUR**

The buffered power supply adapter is designed to powering control panels, sensors, code locks, cameras, consoles, intercoms and other alarm system equipment.

Attention! If the power adaptor is using for continuous work (24H) the rated current of the adaptor should be less than 80% of the maximal current.



SPECIFICATION

Adapter type:	Switching
Input voltage:	230 V AC
Output voltage:	• 11 ... 13.8 V DC (mains mode) • 10 ... 13.8 V DC (battery mode)
Max. output current (total):	3.5 A
Power:	49 W
Battery charging current:	0.5 A / 1 A
Protections:	• Short-circuit • Reverse polarity connection • Overload • Overvoltage • Discharge • Overheat • Tamper
Adapter operation control:	• AC input voltage presence indication • Battery charging indication • DC output voltage presence indication
Place for battery:	12V/17Ah
Max. battery dimensions:	230 x 160 x 90 mm
Housing type:	Metal, hermetic
"Index of Protection":	IP20
Weight:	3.14 kg
Dimensions:	265 x 305 x 101 mm
Manufacturer / Brand:	PULSAR

Guarantee:

2 years

PRESENTATION

Internal view of the housing:



Front view:



Wall mounting side view:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------