

Code: DS-2CD2346G1-I(2.8MM)

## IP CAMERA **DS-2CD2346G1-I(2.8MM)** - 4 Mpx Hikvision

Net: **245.99 EUR** Gross: **245.99 EUR**

IP camera with efficient H.265 / H.264 image compression algorithm for clear and smooth video streaming at maximal resolution of 4 MPx.

PoE powering possibility, compatible with the 802.3af standard makes the device more universal and easier to install.

Powered by Darkfighter - the camera has very good sensitivity, dedicated to poor lighting conditions. Camera is according to IP67 Index of Protection norm.



### SPECIFICATION

|                           |  |
|---------------------------|--|
| Standard:                 | TCP/IP   |
| Sensor:                   | 1/2.7 " Progressive Scan CMOS  |
| Matrix size:              | 4.1 Mpx  |
| Scanning system:          | Progressive  |
| Resolution:               | 2688 x 1520 - 4 Mpx ,<br>1920 x 1080 - 1080p ,<br>1280 x 720 - 720p  |
| Lens:                     | 2.8 mm   |
| View angle:               | <ul style="list-style-type: none"><li>• 104 ° (manufacturer data)</li><li>• 100 ° (our tests result)</li></ul> |
| Range of IR illumination: | 50 m   |
| S/N ratio:                | > 50 dB  |
| RS-485 interface:         | —  |
| Memory card slot:         | Micro SD memory cards up to 128GB support (possible local recording)   |
| Image compression method: | H.265 / H.264 / MJPEG  |
| Alarm inputs / outputs:   | —  |
| Audio:                    | —  |
| Bitrate:                  | 32 kb/s ... 16384 kb/s   |
| Main stream frame rate:   | 25 fps @ 4 Mpx   |
| Network interface:        | 10/100 Base-T (RJ-45)  |

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

|                                |  |
|--------------------------------|--|
| Network protocols:             | TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, IEEE 802.1x, QoS, IPv6, UDP, Bonjour   |
| WEB Server:                    | Built-in   |
| Max. number of on-line users:  | 6  |
| ONVIF:                         | 16.12  |
| Main features:                 | <ul style="list-style-type: none"> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners</li> <li>• ICR - Movable InfraRed filter</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Configurable Privacy Zones</li> <li>• Motion Detection</li> <li>• Mirror - Mirror image</li> <li>• Filtering of false alarms based on the recognition of persons and vehicles</li> <li>• Intelligent image analysis : crossing the line (tripwire), intrusion, detection of entry into the area / exit from the area, scene changing</li> </ul> |
| Mobile phones support:         | Port no.: 8000 or access by a cloud (P2P)<br><ul style="list-style-type: none"> <li>• Android: Free application <a href="#">iVMS-4500</a> or <a href="#">Hik-Connect</a></li> <li>• iOS (iPhone): Free application <a href="#">iVMS-4500</a> or <a href="#">Hik-Connect</a></li> </ul>   |
| Default IP address:            | 192.168.1.64   |
| Default admin user / password: | admin / -<br>The administrator password should be set at the first start   |
| Web browser access ports:      | 80   |
| PC client access ports:        | Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application  |
| Mobile client access ports:    | 8000   |
| Port ONVIF:                    | 80   |
| RTSP URL:                      | <ul style="list-style-type: none"> <li>• Main stream<br/>rtsp://192.168.1.64:554/Streaming/Channels/101/ - RTSP - without authorization<br/>rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ - with authorization</li> <li>• Sub stream<br/>rtsp://192.168.1.64:554/Streaming/Channels/102/ - RTSP - without authorization<br/>rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ - with authorization</li> </ul>  |
| Power supply:                  | <ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 700 mA</li> </ul>   |
| Power consumption:             | <ul style="list-style-type: none"> <li>≤ 10 W @ PoE (802.3af)</li> <li>≤ 8.5 W @ 12 V DC</li> </ul>  |
| Housing:                       | Dome, Metal  |
| Color:                         | White  |
| "Index of Protection":         | IP67   |
| Vandal-proof:                  | —  |
| Operation temp:                | -30 °C ... 60 °C   |
| Weight:                        | 0.73 kg  |
| Dimensions:                    | Ø 139 x 111 mm   |
| Supported languages:           | Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Vietnamese, Italian   |
| Manufacturer / Brand:          | Hikvision  |
| SAP Code:                      | 311305434  |



Guarantee:

3 years

## PRESENTATION

Camera is out from clamping ring:




Memory card slot:



Mounting side view:





In the kit:



## OUR TESTS

Camera image at artificial illumination (about 30Lux):



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Camera image at night conditions with internal built-in IR illuminator on:



Camera image at direct strong light opposite to camera:



## PACKAGE

|                                  |                    |
|----------------------------------|--------------------|
| Dimensions (L x W x H): 0x0x0 mm | Gross Weight: 0 kg |
|----------------------------------|--------------------|