

Code: CD-17A2V2300

CARBON MONOXIDE (CO) DETECTOR **CD-17A2V2300** EL HOME

Net: **95.51 PLN** Gross: **95.51 PLN**

The device is designed for continuous monitoring of CO (carbon monoxide) concentration in the air as well as detection and alarming when the maximum safe concentration of this gas is exceeded. The CD-17A2V2300 detector uses a high-tech electrochemical sensor (10 years of life) and an electronic control chip, allowing it to achieve a high detection rate with low power consumption.

Gas concentration above the threshold level triggers visual and audible alarm signals. Device should be mounted at a height of about 0.7 ... 1.5 m above the floor.



SPECIFICATION

Detection:	Carbon Monoxide (CO)
Alarm signaling:	<ul style="list-style-type: none">• Buzzer• Blinking LED
Gas concentration to trigger alarm:	<ul style="list-style-type: none">• 300 ppm for max. 3 mins• 100 ppm for 10 ... 40 minutes• 50 ppm for 60 ... 90 minutes• 30 ppm for >120 minutes
Main features:	<ul style="list-style-type: none">• Possibility to mount to the wall / standalone• Alarm signaling > 23 ppm• Alarm memory : 7 days• LCD display,• Alarm siren > 85 dB/m @ 3 m• Test mode• Silent mode• Low battery level alarm• Failure signaling• Detector lifetime : 10 years
Power supply:	2 x battery 1.5 V LR6 (AA) (included)
Current consumption:	<ul style="list-style-type: none">• 20 μA (Standby mode)• 50 mA (alarm)
Operation temp:	-10 °C ... 40 °C
Weight:	0.152 kg
Dimensions:	120 x 73 x 34 mm
Manufacturer / Brand:	EL HOME
Guarantee:	2 years

PRESENTATION

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Front panel:



Rear view:



Place for batteries 2 x 1.5V AA:





In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------