

Code: RS2-WE

## WIRELESS MAGNETIC CONTACT **RS2-WE** PYRONIX

Net: 254.00 PLN Gross: 254.00 PLN

The RS2-WE wireless detector (magnetic contact) is used to protection the windows and doors. The detector is also designed to detect the mishandling of security roller blinds.

The device communicates with alarm control panel wirelessly via Pyronix protocol.



### SPECIFICATION

Support:	Wireless alarm systems PYRONIX Enforcer
Detection:	<ul style="list-style-type: none"><li>• Opening the door or window</li><li>• Tamper detection - opening the enclosure, removing from mounting surface</li></ul>
Alarm signaling:	Signal to control panel
Frequency range:	868 MHz Pyronix protocol
Radio communication range (at open area):	max. 1600 m
Alarm inputs:	—
Battery:	3 V CR123A (included)
Backup time:	> 2 years
Environment class:	II
Protection class (Grade):	Grade 2
Main features:	<ul style="list-style-type: none"><li>• Bi-directional encrypted radio communication</li><li>• Terminal for N/C input and/or roller shutter</li><li>• The radio signal level LED indicator</li><li>• 2 wired inputs and 1 tamper input</li></ul>
Operation temp:	-10 °C ... 50 °C
Weight:	0.09 kg
Dimensions:	<ul style="list-style-type: none"><li>• 36 x 117 x 29 mm - Reed switch</li><li>• 13 x 58 x 18 mm - Magnet</li></ul>
Manufacturer / Brand:	PYRONIX

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

SAP Code:	361300059
Guarantee:	2 years

## PRESENTATION

Front view:



Internal view of the housing:



Mounting side view:



In the kit:



## PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------