

Code: CS-HB-70M

MULTI-FUNCTIONAL CCTV TESTER CS-HB-70M

Net: 2 926.82 PLN Gross: 2 926.82 PLN

Multi-functional tester of AHD, HD-CVI, HD-TVI, IP cameras, analog cameras, Speed Dome (PTZ) cameras has implemented many additional functions, necessary during initialization of the CCTV installation system.



SPECIFICATION

Video standard:	AHD-H, HD-CVI, HD-TVI, TCP/IP, PAL, NTSC
Display:	7 " - capacitive touch screen, 1024 x 600 px
Video input:	<ul style="list-style-type: none">• 1 pcs AHD / CVI / TVI - BNC socket• 1 pcs Composite Video (CVBS) - BNC socket
Video output:	<ul style="list-style-type: none">• 1 pcs Composite Video (CVBS) - BNC socket• 1 pcs HDMI
Port LAN:	2 pcs - PoE cameras and switches support
Audio input:	1 pcs Mini Jack
Audio output:	1 pcs Mini Jack
Video signal level meter:	mV (for PAL) IRE (for NTSC)
Video signal generator:	<ul style="list-style-type: none">• Test signal generator• Eight color-bars generating in multi-tv-system modes• It is possible to generate the red, white, black, blue or green screen image
Serial ports:	RS-232, RS-485
Protocols:	Support for over 30 RS485 protocols : Pelco-D, Pelco-P, SAMSUNG SAMSUNG SPD, PANASONIC, LILIN, YAAN, LG Multix, ALEC, Santachi, VICON, Fastrax, MOLYNX, Bosch OSRD, Hikvision, Siemens, Sony-EVI
Baud rates:	150, 300, 600, 1200, 2400, 4800, 9600, 19200, 38400, 115200 b/s
LAN (twisted-pair) or telephone cables testing:	UTP cables or phone lines connecting test with RJ-45 connectors
RS-485, RS-232 lines test:	Data analysis from control device (the commands are displayed in hexadecimal)
Wi-Fi Module:	✓
Identification the wire in the group of wires:	✓
Audio test:	✓
Digital multimeter:	Measurement : voltage, current, resistance, continuity test, diode test, electrical capacity
Optical power measurement:	—

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

TDR reflectometer:	—
Operation as power source:	<ul style="list-style-type: none"> • 12 V DC / 2 A • 5 V DC / 2 A from USB port • 48 V (PoE, LAN), 24 W
Battery power supply:	<ul style="list-style-type: none"> • Battery 6600 mAh • 12 V DC / 2 A (power adapter included)
Estimated battery operation time:	max. 16 hours
Operation:	Graphical menu - touch control and by using the buttons
Main features:	<ul style="list-style-type: none"> • AHD cameras test • HD-CVI cameras test • HD-TVI cameras test • PAL/NTSC cameras test • IP cameras test • Searching and view of IP cameras compatible with Onvif • Motor units and PTZ (Speed Dome) cameras control • IP cameras view from embedded applications - gDMSS HD Lite, iVMS-4500 HD, BSR MPlayer, Easy Mobile, MEye, NetVideo, PT-VSS, Wision, TSee, iCam Player, gDMSS Plus • Test signal generator • LAN connections monitoring • IP addresses scanner • PING - test the link using ICMP packets • Detection of the connected port in switch • LAN (twisted-pair) cables testing • PoE cameras and switches support • PoE power meter • DC 5V / 12V / 48V power source • Identification the wire in the group of wires • Digital Multimeter • Data monitor - serial port data analysis (RS-485 or RS-232) • Audio test • Video recording to micro SD card with playback possibility - 4 GB included • Playback the records • Calculator • Flashlight built-in
Operation temp:	-10 °C ... 50 °C
Permissible relative humidity:	30 % ... 90 %
Weight:	1.18 kg
Dimensions:	254 x 176 x 55 mm
Supported languages:	English, Chinese Simplified, Chinese Traditional, Korean, Polish, Russian, Italian
Guarantee:	2 years

PRESENTATION

Front panel (main menu options visible):



Bottom view:

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
 POL; 60-713 Poznań; Graniczna 10
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Top view:



Rear view:



Main menu:



In the kit:



The tester with accessories housed in a handy bag:



OUR OPINIONS



- Attention! The device is not intended to continuous work 24/7.

PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------