

Code: SO-MF5-B

PROXIMITY READER WITH KEYPAD **SO-MF5-B** SATEL

Net: 495.00 PLN Gross: 495.00 PLN

Outdoor proximity cards and key-fobs reader.



SPECIFICATION

Cards support:	13.56 MHz S50 : Ultralight CSN/SSN, Classic CSN/SSN/MSN, DESFire (EV1 / EV2 / EV3) CSN/MSN
Reading distance of prox-keys:	max. 5 cm
Relay output:	1 pcs
Relay contacts rating (resistive load):	1 A / 30 V
Keyboard built-in:	✓
Autonomous operation:	✓
Operation modes:	<ul style="list-style-type: none">• Partition keypad in the INTEGRA alarm system• The keypad with proximity card reader in the ACCO NET or ACCO access control system• Wiegand Reader• standalone door control module
Doorbell button:	F1 button
Tamper output:	✓
Communication:	<ul style="list-style-type: none">• Wiegand 26-66bit• Open Supervised Device Protocol (OSDP)• RS-485
Main features:	<ul style="list-style-type: none">• Tamper protection (detection of removing from mounting surface and enclosure opening)• LED indication• Beep signal• Manual or computer programming• Keypad backlight buttons

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Power supply:	12 V DC
Average current consumption:	65 mA
Operation temp:	25 °C ... 55 °C
Permissible relative humidity:	max. 93 %
"Index of Protection":	IP67
Color:	Black
Weight:	0.09 kg
Dimensions:	128 x 45 x 21 mm
Manufacturer / Brand:	SATEL
Guarantee:	2 years

PRESENTATION

Front panel:



Internal view:



Rear view:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

