



	IP CAMERA BCS-L-TIP15FSR3-A11 - 5 Mpx 2.8 mm BCS Line	IP CAMERA IPC2105SB-ADF16KM-I0 - 5 Mpx 1.68 mm UNIVIEW
		
	1019.00 PLN 1019.00 PLN	1450.00 PLN 1450.00 PLN
Standard	TCP/IP	TCP/IP
Sensor	1/2.7 " Progressive Scan CMOS	1/2.7 " Progressive Scan CMOS
Matrix size	5 Mpx	5 Mpx
S/N ratio	...	> 56 dB
Resolution	2592 x 1944 - 5 Mpx , 2688 x 1520 - 4 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p	2880 x 1620 - 5 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p
Lens	2.8 mm	1.68 mm
View angle	97 °	180 °
Range of IR illumination	30 m	20 m
RS-485 interface	—	—
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)	Micro SD memory cards up to 256GB support (possible local recording)
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	Ultra 265 / H.265 / H.264 / MJPEG
Alarm inputs / outputs	—	—
Audio	<ul style="list-style-type: none"> • Microphone built-in • Audio detection 	<ul style="list-style-type: none"> • Microphone built-in • Audio transmission via network • Audio detection
Main stream frame rate	20 fps @ 5 Mpx 25 fps @ 4 Mpx	25 fps @ 5 Mpx
Network interface	10/100 Base-T (RJ-45)	10/100 Base-T (RJ-45)
Network protocols	...	IPv4/IPv6, IGMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, HTTP, HTTPS, SMTP, IEEE 802.1x, SNMP, QoS
WEB Server	Built-in	Built-in
Max. number of on-line users	20	32
ONVIF	21.12	✓
Mobile phones support	Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application BCS Manager • iOS (iPhone): Free application BCS Manager 	Access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application EZView • iOS (iPhone): Free application EZView
Default IP address	192.168.1.108	DHCP or 192.168.1.13
Default admin user / password	admin / - The administrator password should be set at the first start	admin / 123456
Web browser access ports	80, 37777	80, 554
PC client access ports	37777	Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation
Mobile client access ports	37777	80
Port ONVIF	80	80

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

RTSP URL	rtsp://admin.haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin.haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream
Main features	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • SSA - Smart Scene Adaptive - intelligent scene adaptation by automatically adjusting the exposure parameters to obtain a better image • SMD PLUS - searching for an object classified as: human, motor vehicle • NAS - Network Attached Storage support • BLC/HLC - Back Light / High Light Compensation • Day/night mode • ICR - Movable InfraRed filter • Auto White Balance • AGC - Automatic Gain Control • Possibility to change the resolution, quality and bit rate • Mirror - Mirror image • Motion Detection - classification of people and vehicles • Configurable Privacy Zones • IVS analysis : crossing the line (tripwire), intrusion - classification of people and vehicles, scene changing, Audio detection 	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support • BLC/HLC - Back Light / High Light Compensation • Possibility to change the resolution, quality and bit rate • Mirror - Mirror image • Privacy zones - max. 4 • Sharpness - sharper image outlines • Motion detection with human/vehicle silhouette recognition • Intelligent image analysis : crossing the line (tripwire), intrusion, detection of entry into the area / exit from the area
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 460 mA 	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 460 mA
Power consumption	<ul style="list-style-type: none"> • ≤ 6.2 W @ PoE • ≤ 5.5 W @ 12 V 	≤ 5.5 W
Housing	Compact - Metal	Compact, Metal
Color	White	White
"Index of Protection"	IP67	IP67
Vandal-proof	—	—
Operation temp	-40 °C ... 60 °C	-30 °C ... 60 °C
Weight	0.57 kg	0.43 kg
Dimensions	193 x 71 x 67 mm	198 x 71 x 71 mm
Supported languages	Polish, English	Polish, English, Czech, Spanish, Dutch, French, German, Portuguese, Slovak, Hungarian, Italian
Manufacturer / Brand	BCS Line	UNIVIEW
Guarantee	3 years	3 years