



	ACCESS POINT +ROUTER MAX18 Wi-Fi 6, 2.4 GHz, 5 GHz 574 Mbps + 1201 Mbps DAHUA	ACCESS POINT +ROUTER ARCHER-VR400 VDSL / ADSL 300 Mbps + 867 Mbps
		
	288.00 PLN 288.00 PLN	337.98 PLN 337.98 PLN
Frequency range	2.4 GHz, 5 GHz	<ul style="list-style-type: none"> • 2.4 GHz, • 5 GHz
Antenna type	<ul style="list-style-type: none"> • 2.4 GHz : 2 x pcs Omnidirectional antenna - built-in • 5 GHz : 2 x Omnidirectional antenna - built-in 	...
Standards	<ul style="list-style-type: none"> • LAN : IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, • Wi-Fi : IEEE 802.11 b/g/n/ac/ax 	IEEE 802.11 b/g/n, IEEE 802.11 a/n/ac, IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, ITU G.993.2, ITU-T G.993.5 (G.vector), ITU-T G.998.4 (G.INP), Full-rate ANSI T1.413 Issue 2, ITU-T G.992.1(G.DMT), ITU-T G.992.2(G.Lite), ITU-T G.994.1 (G.hs), ITU-T G.995.1, ITU-T G.992.3 (G.DMT.bis), ITU-T G.992.4 (G.lite.bis), ITU-T G.992.5
Power consumption	≤ 12 W	...
LAN ports	3 x 10/100/1000 Mbps	3x RJ-45 (10/100 Mbps, Auto MDI/MDX) 1x RJ-45 (10/100/1000 Mbps, Auto MDI/MDX)
WAN interface	...	1x RJ-11, ADSL / ADSL2 / ADSL2+ / VDSL / VDSL2
Transmitter power	...	< 20 dBm @ 2.4 GHz , < 23 dBm @ 5 GHz
Baud rates	574 Mbps + 1201 Mbps	300 Mbps @ 2.4 GHz + 867 Mbps @ 5 GHz
DHCP server	...	✓
Firmware update	...	✓
DDNS	...	✓

Protections	WPA2	<ul style="list-style-type: none"> • LAN : Firewall, MAC addresses filtering, IP addresses filtering, parental control, LAN ACL • WLAN : WEP 64/128-bit, WPA-PSK/WPA2-PSK, TKIP/AES
Management interface	...	Web browser
Main features	<ul style="list-style-type: none"> • Support for Mesh technology, • Wi-Fi 6 support - a standard that offers higher speeds, better performance in high-traffic environments • Port Security : Contact/Air (ESD/EMP) ± 8 kV / ± 6 kV • Easy and uniform management system for many devices - WiLynk application • Intuitive installation and configuration of many advanced functions 	<ul style="list-style-type: none"> • Firewall • Internet access filtering • Static / dynamic routing • Built-in 4-port switch • Wireless transmission statistics • The WPS function allows to easy establish an encrypted connection • QoS • WMM (Wi-Fi Multimedia) • Rate limit • Access control • Remote management • DMZ • parental control • Guest Network - a separate and secure network for guests • 1 x Port USB 2.0 • The DSL line splitter included
Operation temp	-10 °C ... 55 °C	0 °C ... 40 °C
Permissible relative humidity	5 % ... 95 %	max. 90 % (max)
Power supply	12 V DC / 1.5 A (power adapter included)	12 V DC / 1.5 A (power adapter included)
Weight	0.23 kg	0.32 kg
Dimensions	95 x 95 x 73 mm	216 x 125 x 32 mm
Manufacturer / Brand	DAHUA	TP-LINK
Guarantee	2 years	2 years