


	POWER DISTRIBUTION UNIT PR-1.5M-4G/B (4 OUTLETS) 1.3 m	4-CHANNEL REMOTE CONTROL UREMOTE-BASIC/BLEBOX Wi-Fi	ROUTER TL-WR844N 300 Mbps TP-LINK
			
	15.28 PLN 15.28 PLN	121.15 PLN 121.15 PLN	66.67 PLN 66.67 PLN
Frequency range	2.412 GHz ... 2.472 GHz
Rated voltage	220 ... 240 V AC / 50 Hz
Antenna type	2 x 5 dBi Omnidirectional antenna
Total maximal current	10 A
Standards	IEEE 802.11 b/g/n
Maximal total load	2500 W
Baud rates	300 Mbps
Number of outlets	4 grounded outlets 10A/250V CEE 7/5
Fuse	—
Switch	—
Wireless	...	Wi-Fi, 2.4 GHz - IEEE 802.11g	...
Wire gauge	3 x 1.5 mm ²
Length of the cable	1.3 m
Operation range	...	≤ 100 m (in open area) ≤ 40 m (internal)	...
LAN ports	• 1 x 10/100 Mbps - WAN, • 4 x 10/100 Mbps - LAN
Mobile phones support	...	• The wBox free application on Android • The wBox free application on iOS	...
LED indicators	LAN, INTERNET, WiFi
Receiver sensitivity	• 270M : -70 dBm @ 10% PER • 130M : -74 dBm @ 10% PER • 108M : -74 dBm @ 10% PER • 54M : -77 dBm @ 10% PER • 11M : -87 dBm @ 10% PER • 6M : -90 dBm @ 10% PER • 1M : -98 dBm @ 10% PER
Housing	Plastic	Plastic (ABS)	...
DDNS	• No-IP • DynDNS

Color	Black	Black	...
DHCP server	✓
Firmware update	✓
Operation modes	Router, Access Point, Range Extender, WISP
Protections	<ul style="list-style-type: none"> • WEP, WPA/WPA2, WPA-PSK/WPA2-PSK, WPA2-Enterprise, IEEE 802.1x • SPI network firewall • Table of access / access-deny according to MAC addresses of client cards • Hardware supports IP + MAC binding based on port
Management interface	Web browser, Tether application
Transmitter power	max. 20 dBm
Main features	...	<ul style="list-style-type: none"> • Number of buttons : 4 • 4 independent channels, • 4 groups, • Number of supported devices : 3 / Channel, • Controlling BleBox devices • Order confirmation • LED indication • Bidirectional communication • Transmission encryption • µWiFi technology support • Control possible without Wi-Fi network available 	<ul style="list-style-type: none"> • RESET button • Built-in 4-port switch • Guest Network - a separate and secure network for guests • 2x2 MIMO • Smooth transmission in HD quality - IGMP Proxy/Snooping, Bridge VLAN, Tag VLAN functions contribute to optimal IPTV transmission • MAC address cloning • Firewall • Internet access filtering • parental control • Access control • Static / dynamic routing • WAN : PPPoE, PPTP, L2TP • QoS : WMM (Wi-Fi Multimedia) • Port forwarding • DMZ • DHCP client list • IPv4/IPv6
Power supply	...	<ul style="list-style-type: none"> • built-in battery - lithium-polymer • 5 V micro USB (battery charging) • Estimated battery operation time : 2 years 	5 V DC / 0.6 A (power adapter included)
Operation temp	...	-20 ... 50 °C	0 °C ... 40 °C
Permissible relative humidity	10 % ... 90 % (non-condensing)
Weight	0.26 kg	0.028 kg	0.12 kg

Dimensions	196 x 54 x 39 mm	72 x 39 x 12 mm	115 x 107 x 25 mm
Manufacturer / Brand	...	BleBox	TP-LINK
Guarantee	2 years	2 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00