



	ACCESS CONTROLLER MODULE MC16-PAC-ST-2 ROGER	ACCESS CONTROLLER PR311SE-BK ROGER
		
	1390.00 PLN 1390.00 PLN	450.00 PLN 450.00 PLN
Cards support	...	Unique EM 125kHz
Number of served transitions	2 (two-way)	...
Reading distance of prox-keys	...	max. 15 cm
Number of supported readers	8	...
Keyboard built-in	...	—
Number of users	unlimited (purchase of the appropriate license required)	...
Number of media per ID	8 - Proximity card, PIN code, fingerprint, etc.	...
Selected features of the standalone mode	...	<ul style="list-style-type: none"> • 1000 indexed users • Operation with XM-2 I/O extension module (Full Standalone Mode)
Buffer memory	8 000 000 events buffer	...
Number of access zones	4	...
Number of alarm zones	4	...
Battery backup support	12 V / 7 Ah	...
Communication	<ul style="list-style-type: none"> • Ethernet - RJ-45 socket • RACS 5 v2 (Roger) • RS-485 interface 	<ul style="list-style-type: none"> • RS-485 • RACS (Roger)

Main features	<ul style="list-style-type: none"> • Integrated support in VISO ST software • Functions in the VISO ST system: <ul style="list-style-type: none"> - MSSQL database - work in distributed systems - multi-station work - monitoring of transitions with video preview - T&A event reporting - maximum number of transitions in the system : 128 	<ul style="list-style-type: none"> • The ability to add additional reader (bilateral way door control), • 3 programmable input lines NO/NC, • 2 programmable transistor outputs 1A, • One programmable relay output 1.5A/30V, • Door modes (Normal, Locked, Unlocked and Conditionally Unlocked), • Any topology of communication bus, • "Guest" type additional users support defined individually on each controller, • Integration with an alarm system via in/out line ,
Average current consumption	...	50 mA
Power supply	<ul style="list-style-type: none"> • 17 ... 22 V AC • 10 ... 15 V DC • 22 ... 26 V DC 	10 ... 15 V DC
Operation temp	5 °C ... 40 °C	-25 °C ... 60 °C
Permissible relative humidity	10 % ... 95 % (non-condensing)	10 ... 95 % (non-condensing)
Weight	0.14 kg	0.18 kg
Dimensions	175 x 72 x 30 mm	152.5 x 46 x 23 mm (Standard housing stand) 152.5 x 46 x 35 mm (Thicker housing stand)
Manufacturer / Brand	ROGER	ROGER
Guarantee	3 years	3 years