

	ACCESS CONTROLLER DS-K1T804BMF Hikvision	ACCESS POINT 5.8 GHz CDS-6IP/ECO CAMSAT	ACCESS POINT 4G LTE +ROUTER ATE-G1CH 150Mb/s AUTONE
			
	819.00 PLN 819.00 PLN	639.00 PLN 639.00 PLN	366.40 PLN 366.40 PLN
Cards support	13.56 MHz S50	...	...
Reading distance of prox-keys	0 ... 4.5 cm	...	...
Autonomous operation	✓	...	...
Keyboard built-in	✓	...	...
Doorbell button	✓	...	...
Frequency range	...	5180 MHz ... 5350 MHz , 5470 MHz ... 5725 MHz	2.4 GHz
Tamper output	✓	...	...
RS-485 interface	—	...	...
Communication	Wiegand	...	...
Standards	...	...	IEEE 802.11 b/g/n, 4G LTE, 3G
Identification time	< 1 s	...	...
Network interface	• RJ-45 - 10/100 Base-T • Built-in Wi-Fi module	...	...
Default IP address	192.0.0.64	...	...
Default admin user / password	admin / -	...	...
Transmitter power	...	≤ 500 mW (27 dBm)	...
LAN ports	...	...	1 x 10/100 Mbps - LAN
Wireless transmission range	...	max. 2 km	...
Antenna type	...	Integrated, 2 pcs 14 dBi MIMO - Interpolarized H/V	• Omnidirectional antenna Wi-Fi - 5 dBi, • 2 x Omnidirectional antenna 4G LTE
Modulation type	...	OFDM	...
Baud rates	...	max. 60 Mbps	11n : 150 Mbps 11g : 54 Mbps 11b : 11 Mbps LTE : 150 / 50 Mbps
Operation modes	...	• Video Bridge - mode dedicated to work with IP cameras • Master - Access Point • Slave - AP Client	...
Housing	Plastic	...	...
Vandal-proof	—	...	...

Color	Black	...	...
Power consumption	...	≤ 11 W	...
SAP Code	302918016	...	...
Network type	...	...	• 4G : FDD-LTE, WCDMA/HSPA+ B1/B3/B5/B7/B8/B20 - 2100 / 1800 / 2600 / 900 / 800 / 700 MHz • 4G : TDD-LTE B38/B40/B41 - 2600 / 2300 / 2500 MHz • 3G : UMTS/HSPA+ - 2100 / 900 MHz
LTE	...	...	✓
QSS	...	...	—
WDS	...	...	—
DHCP server	...	...	✓
Protections	...	• 64 / 128 / 152 bits WEP code • WPA • WPA-PSK/WPA2-PSK	• WPA-PSK/WPA2-PSK • SSID hiding • MAC addresses filtering
Management interface	...	...	Web browser
Main features	• Color LCD : 2.4 ", 320 x 240 px • Memory of 3000 fingerprint patterns • Memory of 3000 RFID cards • History of 100 000 events • Full support via network • Counter of the door opening time with the possibility of sending an alarm signal after exceeding the set value • Door contact and request button for exit inputs • Alarm inputs / outputs : 1 / 1 • Port USB	• Operates in configuration Point-to-Point and Point-to-Multipoint • MIMO technology - increases the throughput of wireless link (multiple antennas transmission) • Bidirectional communication • IP PTZ control • RF power control • interference free transmission (industrial, 802.11, Bluetooth, radiotelephony, etc.)	• SIM socket • DHCP client/server support • DHCP client list • Static routing • Default address : 192.168.100.1
Power supply	12 V DC / 1 A (power adapter included)	• Passive PoE : 48 V DC (using an external adapter) • 12 V DC / 1 A (power adapter included)	12 V DC / 2 A (power adapter included)
Operation temp	-10 °C ... 55 °C	-20 °C ... 70 °C	0 °C ... 40 °C
Permissible relative humidity	10 ... 90 % (non-condensing)	...	10 % ... 90 % (non-condensing)
"Index of Protection"	—	IP55	IP66
Weight	0.44 kg	0.35 kg	0.16 kg
Dimensions	205 x 77 x 37 mm	249 x 88 x 52 mm	132 x 132 x 50 mm

Manufacturer / Brand	Hikvision	CAMSAT	AUTONE
Guarantee	3 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00