

	<a href="#">SMART SWITCH M/ROW-02 Wi-Fi SUPLA 230 V AC ZAMEL</a>	<a href="#">CONNECTOR WITH ELASTIC SEALING F/5.9-G</a>	<a href="#">AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HDW1801TLM-IL- A-0280B-S2 - 8.3 Mpx 4K UHD 2.8 mm DAHUA</a>
			
	332.05 PLN 332.05 PLN	0.51 PLN 0.51 PLN	590.00 PLN 590.00 PLN
Support	SUPLA	...	...
Connector type	...	"F" Straight plug	...
Attachment of connector elements	...	Twisted-on	...
Application	Lighting control, switching devices on/off	...	...
Shield fastening	...	Twisting-on	...
Number of pins	2 x NO	...	...
Standard	...	...	AHD, HD-CVI, HD-TVI, CVBS
Wire mounting	...	—	...
Sensor	...	...	Progressive Scan CMOS
Application	...	Coaxial cable	...
Matrix size	...	...	8.3 Mpx
Cable diameter	...	max. 5.9 mm	...
Number of inputs	2	...	...
Impedance	...	75 Ω	...
Number of outputs	2	...	...
Material	...	Metal	...
Rated voltage	230 V AC	...	...
Example of application	...	RG59	...
Total maximal current	5 A	...	...
Maximal total load	1250 VA	...	...
Maximal outputs load	<ul style="list-style-type: none"> <li>• 750 W (single output) - light bulbs and halogen lamps</li> <li>• 250 W (single output) - CFL fluorescent lamps</li> <li>• 60 W (single output) - LED bulbs</li> </ul>	...	...
Connector type	screw terminals	...	...
Wireless	Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n	...	...
Mobile phones support	<ul style="list-style-type: none"> <li>• The <a href="#">SUPLA</a> free application on Android</li> <li>• The <a href="#">SUPLA</a> free application on iOS</li> </ul>	...	...

Resolution	...	...	3840 x 2160 - 8.3 Mpx 4K UHD @ HD-CVI / HD-TVI / AHD @ 15 fps , 2592 x 1944 - 5 Mpx @ HD-CVI @ 25 fps , 2560 x 1440 - 3.7 Mpx @ HD-CVI @ 25 fps , 1920 x 1080 - 1080p @ HD-CVI @ 25 fps , 960 x 576 - 960H @ PAL @ 25 fps
Lens	...	...	2.8 mm
View angle	...	...	• 106 ° (manufacturer data) • 101 ° (our tests result)
Range of IR illumination	...	...	20 m
Main features	<ul style="list-style-type: none"> <li>• Control from a Web browser,</li> <li>• Local control by physical button,</li> <li>• schedule,</li> <li>• timer,</li> <li>• remote access,</li> <li>• voice control,</li> <li>• Possibility to manually program scenarios from the built-in API,</li> <li>• Built-in electricity consumption monitor</li> </ul>	<ul style="list-style-type: none"> <li>• Wide frequency range</li> <li>• Corrosion resistance</li> <li>• Elastic sealing</li> </ul>	...
White light LED illuminator range	...	...	20 m
IR illuminator power adjustment	...	...	Automatic
Operation temp	-10 °C ... 55 °C	...	...
Video output	...	...	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω
Audio	...	...	• Microphone built-in, • Audio support via coaxial cable - HD-CVI only
OSD menu	...	...	✓

Main features	...	...	<ul style="list-style-type: none"> <li>• Smart Dual Illumination technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality</li> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• ICR - Movable InfraRed filter</li> <li>• AGC - Automatic Gain Control</li> <li>• Privacy zones - max. 8</li> <li>• Mirror - Mirror image</li> <li>• Auto White Balance</li> <li>• Sharpness - sharper image outlines</li> </ul>
Power supply	...	...	12 V DC / 350 mA
Power consumption	...	...	≤ 4.2 W
Housing	Plastic	...	Dome - Metal
Color	Green	...	White
"Index of Protection"	IP20	...	IP67
Vandal-proof	...	...	—
Operation temp	...	...	-40 °C ... 60 °C
Weight	0.03 kg	0.0032 kg	0.33 kg
Dimensions	40 x 38 x 17 mm	Ø 11 mm x 20 mm	Ø 94 x 86 mm
Manufacturer / Brand	ZAMEL	...	DAHUA
Guarantee	2 years	2 years	3 years