



	PLUG-IN MODULE FOR OVERVOLTAGE LIMITER LE-412297 2 TYPE 20 kA LEGRAND	WI-FI SMART PLUG ABAX/ABAX2 ASW-200-E 2300 W SATEL
		
	22.79 CHF 22.79 CHF	59.10 CHF 59.10 CHF
Rated voltage	230 / 400 V AC, 50 / 60 Hz	230 V AC, 50 / 60 Hz
Maximal voltage	320 V AC, 50 / 60 Hz	...
Maximal total load	...	2300 W
Total maximal current	...	10 A
Power consumption	...	1 W (Standby mode)
Class	2 type (Class C)	...
Number of outlets	...	1 pcs
Protection level Up	1.2 kV @ 8/20 μs (T2)	...
Socket type	...	CEE 7/5 (EURO)
Nominal discharge current	5 kA @ 8/20 μs (T2)	...
Plug type	...	CEE 7/7
Grounding	...	✓
Maximum stroke current	20 kA @ 8/20 μs (T2)	...
Operation state indication	✓	...
Wireless	...	Satel ABAX/ABAX2, 868.0 ... 868.6 MHz

Main features	Varistor	<ul style="list-style-type: none"> • Remote update of software, • Remote configuration, • Bi-directional encrypted radio communication - AES, • Frequency hopping against jamming for reliable transmission, • LED indication - Current consumption / Failure signaling • Operation modes : manual / manual or remote access / manual or remote access (blocking function) • ON/OFF button • Operating range in open area : 1000 m ABAX2, 500 m ABAX • Protections : Overload, Overheat • Easy operation • Environmental class EN 50130-5 : II • Supported norms : EN50130-4, EN50130-5
Housing	Plastic	Plastic
Color	...	Light gray
Operation temp	...	-10 °C ... 55 °C
Permissible relative humidity	...	max. 93 % ± 3 %
Weight	0.042 kg	0.060 kg
Dimensions	62 x 54 x 17 mm	Ø 45 x 70 mm
Manufacturer / Brand	LEGRAND	SATEL
Guarantee	2 years	2 years