



	CONNECTOR WITH ELASTIC SEALING F/5.9-G	SWITCHING ADAPTER APS-055 SATEL
		
	0.51 PLN 0.51 PLN	86.00 PLN 86.00 PLN
Adapter type	...	Switching
Connector type	"F" Straight plug	...
Power voltage	...	195 ... 265 V AC
Attachment of connector elements	Twisted-on	...
Frequency range	...	50 Hz
Shield fastening	Twisting-on	...
Wire mounting	—	...
Output voltage	...	5 V DC, stabilized
Application	Coaxial cable	...
Cable diameter	max. 5.9 mm	...
Maximal load	...	0.5 A
Impedance	75 Ω	...
Output power	...	4 W
Material	Metal	...
Number of outputs	...	2 pcs
Example of application	RG59	...
Efficiency	...	≤ 72 %
Protections	...	<ul style="list-style-type: none"> • Input : Short-circuit, DC filter to eliminate interferences • Output : Short-circuit, Overload
Main features	<ul style="list-style-type: none"> • Wide frequency range • Corrosion resistance • Elastic sealing 	<ul style="list-style-type: none"> • IEC 38 compliance • Can be installed in a 60mm electrical box
Environment class	...	II
Housing type	...	Plastic
Operation temp	...	-10 °C ... 55 °C
Weight	0.0032 kg	0.036 kg
Dimensions	Ø 11 mm x 20 mm	47 x 47 x 22 mm
Manufacturer / Brand	...	SATEL
Guarantee	2 years	2 years