

	<a href="#">SMART CONTROLLER FOR ROLLER SHUTTERS SRW-03 Wi-Fi, 230 V AC ZAMEL</a>	<a href="#">SWITCH POE IP-9-11-L2 8-PORT ATTE</a>	<a href="#">HUB USB 3.0 H1208B</a>
			
	433.25 PLN 433.25 PLN	753.11 PLN 753.11 PLN	21.46 PLN 21.46 PLN
Support	SUPLA	...	...
Application	roller shutters, roof windows, awnings, drop-down screens, curtains	...	...
Connectors	...	...	<ul style="list-style-type: none"> <li>• 1 x plug - USB-C</li> <li>• 4 x socket - USB-A</li> </ul>
Length of the cable	...	...	18 cm
Number of pins	7 x NO ( 6 x Motor + 1 x Power output )	...	...
USB standard	...	...	3.0
Rated voltage	230 V AC	...	...
LAN ports	...	<ul style="list-style-type: none"> <li>• 1 x RJ45 10/100 Base-T - Uplink</li> <li>• 9 x RJ45 10/100 Base-T + PoE (802.3af/at) / Passive PoE</li> </ul>	...
Total maximal current	5 A	...	...
Maximal total load	1250 VA	...	...
Connector type	screw terminals	...	...
Management	...	—	...
LED diodes	...	Power, LAN	...
Wireless	Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n	...	...
Mobile phones support	<ul style="list-style-type: none"> <li>• The <a href="#">SUPLA</a> free application on Android</li> <li>• The <a href="#">SUPLA</a> free application on iOS</li> </ul>	...	...
Transmission speed	...	10 / 100 Mbps : 1 Port LAN + 9 LAN & PoE ports	...
Maximal output power	...	<ul style="list-style-type: none"> <li>• 40 W @ Passive PoE - 1 ... 4 ports,</li> <li>• 70 W @ Passive PoE - Port 5,</li> <li>• 30 W @ PoE (802.3af/at) - 1 ... 5 ports</li> </ul>	...
Housing	Plastic	...	...
Maximal total power	...	96 W	...
"Index of Protection"	IP20	...	...

Color	Green	...	...
Operation temp	-10 °C ... 55 °C	...	...
Operation modes	...	<ul style="list-style-type: none"> <li>• Normal : 100 m @ 10/100 Mb/s - 1 ... 5 ports</li> <li>• Long Range : 280 m @ 10 Mb/s - 1 ... 4 ports ; 100 m @ 10/100 Mb/s - Port 5</li> </ul>	...
Main features	<ul style="list-style-type: none"> <li>• schedule,</li> <li>• timer,</li> <li>• remote access,</li> <li>• voice control,</li> <li>• Possibility to manually program scenarios from the built-in API,</li> <li>• Wall mounting</li> </ul>	<ul style="list-style-type: none"> <li>• Possible cascading device connection (power transmission between devices using Passive PoE via LAN 5 port)</li> <li>• The LAN 5 (PoE IN/OUT) port can be used to power PoE devices as well as to draw power from other devices</li> <li>• The output PoE voltage is equal to the input voltage</li> <li>• The ability to independently turn on and off the PoE power for each of the LAN 1 ... LAN 5 ports</li> <li>• The modular design streamlines service tasks and enables quick and easy system expansion</li> <li>• The raster system of module assembly facilitates the expansion of the device by further modules</li> <li>• The ABOX-L2 mounting enclosure is equipped with 11 cable entries with glands in the 10 x M16 + 1 x M20 arrangement</li> </ul>	Solid workmanship
Power supply	...	230 V AC - cable terminals	...
Weight	0.173 kg	1.05 kg	0.03 kg
Dimensions	167 x 53 x 39 mm	248 x 222 x 96 mm	88 x 17 x 9 mm
Manufacturer / Brand	ZAMEL	ATTE	UNITEK
Guarantee	2 years	3 years	2 years