

	<a href="#">IP CAMERA DS-2CD1067G2H-LIU(2.8MM) ColorVu - 6 Mpx Hikvision</a>	<a href="#">IP CAMERA DS-2CD1023G2-I(2.8MM)PL - 1080p Hikvision</a>
		
	880.00 PLN 880.00 PLN	534.00 PLN 534.00 PLN
Standard	IP	IP
Resolution	3200 x 1800 - 6 Mpx , 2688 x 1520 - 4 Mpx , 1920 x 1080 - 1080p 1280 x 720 - 720p	1920 x 1080 - 1080p , 1280 x 720 - 720p
Sensor	1/2.4 " Progressive Scan CMOS	1/2.9 " Progressive Scan CMOS
Lens	2.8 mm	2.8 mm
View angle	115 °	104 °
White light LED illuminator range	30 m	...
Range of IR illumination	30 m	30 m
Memory card slot	—	—
Network interface	...	10/100 Base-T (RJ-45)
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs	—	—
Audio	• Microphone built-in, • Audio transmission via network	—
Main stream frame rate	20 fps @ 6 Mpx	25 fps @ 1080p
Interface	10/100 Base-T (RJ-45)	...
WEB Server	Built-in	Built-in
Max. number of on-line users	6	6
ONVIF	—	✓
Mobile phones support	Port no.: 8000 or access by a cloud (P2P) • Android: Free application <a href="#">Hik-Connect</a> • iOS: Free application <a href="#">Hik-Connect</a>	Port no.: 8000 or access by a cloud (P2P) • Android: Free application <a href="#">Hik-Connect</a> • iOS: Free application <a href="#">Hik-Connect</a>
Default IP address	192.168.1.64	192.168.1.64
Main features	<ul style="list-style-type: none"> <li>• Smart Hybrid Light / ColorVu technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality</li> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• BLC - Back Light Compensation</li> <li>• HLC - High Light Compensation (spot)</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Horizontal mirror image</li> <li>• Smart motion detection (with recognizing people and vehicles)</li> <li>• Configurable Privacy Zones</li> <li>• Sharpness - sharper image outlines</li> <li>• video tampering</li> <li>• Filtering of false alarms based on the recognition of persons and vehicles</li> </ul>	<ul style="list-style-type: none"> <li>• D-WDR - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• Anti-Flicker - The technology eliminates the tiring eyes flickering image effect</li> <li>• EXIR - high-efficiency infrared LEDs technology, which even covers the whole plan of both central vantage points of the scene as well as the corners</li> <li>• BLC - configurable Back Light Compensation</li> <li>• HLC - High Light Compensation (spot)</li> <li>• ICR - Movable InfraRed filter</li> <li>• Day/night mode</li> <li>• Mirror - Mirror image</li> <li>• Configurable Privacy Zones</li> <li>• Smart motion detection (with recognizing people and vehicles)</li> <li>• Sharpness - sharper image outlines</li> </ul>
Default admin user / password	admin / - The administrator password should be set at the first start	admin / -
Web browser access ports	80	80
PC client access ports	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Mobile client access ports	8000	8000
Port ONVIF	80	80
RTSP URL	<ul style="list-style-type: none"> <li>• Main stream :</li> <li>rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/</li> <li>• Sub stream :</li> <li>rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/</li> </ul>	<ul style="list-style-type: none"> <li>• Main stream :</li> <li>rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/</li> <li>- with authorization</li> <li>• Sub stream :</li> <li>rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/</li> <li>- with authorization</li> </ul>
Power supply	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 550 mA</li> </ul>	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 410 mA</li> </ul>
Power consumption	<ul style="list-style-type: none"> <li>• ≤ 8 W @ PoE</li> <li>• ≤ 6.6 W @ 12 V DC</li> </ul>	<ul style="list-style-type: none"> <li>• ≤ 5 W @ 12 V DC</li> <li>• ≤ 6.5 W @ PoE (802.3af)</li> </ul>
Housing	Compact, Metal	Compact - Metal + Plastic
Color	White	White
"Index of Protection"	IP67	IP67
Mechanical protection class	—	...
Operation temp	-30 °C ... 60 °C	-30 °C ... 60 °C
Weight	0.3 kg	0.27 kg
Dimensions	Ø 70 x 173 mm	171 x 70 x 66 mm
Supported languages	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian	Polish
Manufacturer / Brand	Hikvision	Hikvision
SAP Code	311325494	311327275
Guarantee	3 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00