



	NVR NVR4108-8P-EI 8 CHANNELS, 8 PoE WizSense DAHUA	CHARGER POWERBANK XTAR-PB2S 18 W XTAR
		
	1907.00 PLN 1907.00 PLN	74.88 PLN 74.88 PLN
Standard	TCP/IP	...
Supported resolutions	max. 16 Mpx - 4608 x 3472 px	...
Video outputs	1 pcs HDMI 4K 1 pcs VGA	...
Battery type	...	Li-Ion 18650, 18700, 20700, 21700 / 2 pcs
Maximal load power	...	18 W
Audio support	<ul style="list-style-type: none"> • 8 Channels - Audio from cameras • Bi-directional audio streaming support 	...
Number of inputs	...	1 pcs
Audio inputs	1 pcs CINCH	...
Audio outputs	1 pcs CINCH	...
Number of outputs	...	<ul style="list-style-type: none"> • 1 pcs USB-C, • 1 pcs USB-A
Image compression method	Smart H.265+ / H.265 / Smart H.264+ / H.264 / MJPEG	...
Bitrate	max. 256 Mbps	...
Supported hard drives	1 x 16 TB SATA	...
Recording modes	Manual, Motion Detection, Schedule	...
External storage devices backup	Backup to USB drive (pendrive, external drive)	...
Power inputs	...	USB-C socket : 5 V / 2 A ; 9 V / 2 A ; 12 V / 1.5 A - 18 W (max)
Searching and playback the records	<ul style="list-style-type: none"> • Records searching: by time and events type. Records playback: forward, backward, fast, slow • Advanced searching (to the one second accuracy) • Smart Playback function • Records playback from max. 8 channels in the same time @ 4 Mpx (without AI) • Records playback from max. 8 channels in the same time @ 1080p (AI) 	...
Network interface	1 x RJ-45 10/100/1000 Base-TX	...
Network functions	Full support via network, Remote records copying, Web-Server built-in	...
Power outputs	...	<ul style="list-style-type: none"> • 1 pcs USB-A : 5 V / 3 A ; 9 V / 2 A ; 12 V / 1.5 A - 18 W (max) - QC 3.0 & PD 3.0, • 1 pcs USB-C : 5 V / 3 A ; 9 V / 2 A ; 12 V / 1.5 A - 18 W (max) - QC 3.0 & PD 3.0

Protections	...	<ul style="list-style-type: none"> • Overcharge protection • Discharge • Overload • Overvoltage • Short-circuit
Main features	...	<ul style="list-style-type: none"> • Charging Li-ion batteries controlled by a three-stage processor TC/CC/CV charging process • Battery status indicator • Battery status indicator LED
Network protocols	HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, SNMP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, IP Search, P2P, Auto Register	...
ONVIF	22.06	...
Default IP address	192.168.1.108	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Mobile phones support	Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application DMSS • iOS (iPhone): Free application DMSS See how to configure the P2P function in Dahua recorders and how to enable the mobile application	...
Web browser access ports	80, 37777	...
PC client access ports	37777	...
Mobile client access ports	37777	...
RTSP URL	<ul style="list-style-type: none"> • rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream • rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream 	...
USB	2 pcs USB 2.0	...
Serial ports	—	...
Alarm inputs / outputs	—	...
PTZ control	IP Speed Dome Cameras	...
Motion Detection	✓	...
Intelligent image analysis	✓	...

Main features	<ul style="list-style-type: none"> • Intelligent image analysis : crossing the line (tripwire), intrusion, scene changing, face detection • SMD PLUS - searching for an object classified as: human, motor vehicle • Filtering of false alarms based on the recognition of persons and vehicles • Quick Pick - AI technology enabling, together with the recorder, quick identification of interesting objects (people/vehicles) based on an artificial intelligence algorithm. It allows to extract and compare the colors of clothes and vehicles • Face recognition • Face analysis: determination of sex, age and characteristic elements of appearance (glasses, facial hair, mask) • Support for up to 10 face databases, including 20 000 face images • In the base other than face photography, can also be stored such information as: name, sex, date of birth, nationality, address, ID number • Intelligent face search by metadata of different targets or uploading pictures of faces to the device and comparing them with recorded faces by similarity • Privacy zones <p>Functions implemented in cooperation between the recorder and cameras that support these functions :</p> <ul style="list-style-type: none"> • ANPR • people counting • heat map 	...
Mouse support	✓	...
IR remote controller in the set	—	...
Switch PoE	8-port PoE Switch built-in, 25.5 W / Channel - PoE (802.3af/at)	...
Maximum total switch load	72 W	...
Power supply	53 V DC / 1.81 A (power adapter included)	...
Power consumption	max. 10 W (without HDD)	...
Operation temp	-10 °C ... 55 °C	...
Weight	0.69 kg	0.2 kg
Dimensions	270 x 206 x 48 mm	140 x 72 x 14 mm
Supported languages	Polish, English, Bulgarian, Czech, Finnish, Greek, Romanian, Serbian, Slovenian, Hungarian	...
Manufacturer / Brand	DAHUA	XTAR
Guarantee	3 years	2 years