



	<a href="#">IP VANDALPROOF CAMERA IPC-HDBW3849R1-ZAS-PV-27135-S5 TIOC WizSense - 8.3 Mpx 4K UHD 2.7 ... 13.5 mm - MOTOZOOM DAHUA</a>	<a href="#">FLUSH BOX LE-031301 LEGRAND</a>
		
	2804.00 PLN 2804.00 PLN	1.73 PLN 1.73 PLN
Application	...	Arteor, Galea Life, Mosaic, Vela, Valena, Niloé, Kaptika product series
Standard	IP	...
Main features	...	<ul style="list-style-type: none"> <li>• Flush-mounted</li> <li>• 2 fixing points</li> </ul>
Material	...	Plastic
Internal dimensions	...	67 x 62 x 40 mm
Montage hole diameter	...	Ø 80 mm
Resolution	3840 x 2160 - 8.3 Mpx 4K UHD , 3072 x 2048 - 6 Mpx , 3072 x 1728 - 5 Mpx , 2592 x 1944 - 5 Mpx , 2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2048 x 1536 - 3 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p	...
Sensor	1/2.8 " Progressive Scan CMOS	...
Lens	2.7 ... 13.5 mm - Motozoom	...
View angle	108 ° ... 34 °	...
Range of IR illumination	50 m	...
White light LED illuminator range	40 m	...
Min. illumination	0.004 Lux / F1.0 (color)	...
S/N ratio	> 56 dB	...
RS-485 interface	—	...
Memory card slot	Micro SD card support up to 512GB	...
Image compression method	AI H.265 / H.265+ / H.265 / AI H.264 / H.264+ / H.264 / MJPEG	...
Alarm inputs / outputs	1 / 1	...
Audio	<ul style="list-style-type: none"> <li>• Microphone built-in - 2 pcs,</li> <li>• External microphone input,</li> <li>• Audio output</li> <li>• Speaker built-in</li> <li>• Bi-directional audio streaming support</li> <li>• Audio detection</li> </ul>	...
Main stream frame rate	25 fps @ 8.3 Mpx	...
Network interface	10/100 Base-T (RJ-45)	...
WEB Server	Built-in	...
Max. number of on-line users	20	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

ONVIF	✓	...
Mobile phones support	Port no.: 37777 or access by a cloud (P2P) • Android: Free application <a href="#">DMSS</a> • iOS (iPhone): Free application <a href="#">DMSS</a>	...
Default IP address	192.168.1.108	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Web browser access ports	80, 37777	...
PC client access ports	37777	...
Mobile client access ports	37777	...
Port ONVIF	80	...
RTSP URL	rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream	...
Intelligent image analysis	<ul style="list-style-type: none"> <li>• crossing the line (tripwire) - classification of people and vehicles</li> <li>• intrusion - classification of people and vehicles</li> <li>• scene changing</li> <li>• video tampering</li> </ul>	...
Main features	<ul style="list-style-type: none"> <li>• Active deterrence function, Alternately flashing LEDs: red and blue - frequency configuration, Siren sound - 3 volume levels</li> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• AcuPick support - technology that uses artificial intelligence on both front-end and back-end to search through massive amounts of video data to quickly locate targets with high precision</li> <li>• SMD 4.0 - searching for an object classified as: human, motor vehicle - increased detection distance and resistance to false alarms</li> <li>• AI SSA AI Smart Scene Adaptive - scene auto-adaptation using deep learning algorithms to detect environmental conditions such as rain, fog, backlight, low light and flickering, in order to set the optimal image parameters</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• Day/night mode</li> <li>• Full Color - colorful night mode</li> <li>• Auto White Balance</li> <li>• AGC - Automatic Gain Control</li> <li>• Motion Detection - max. 4 zones</li> <li>• Privacy zones - max. 8</li> <li>• Image rotation and mirror</li> <li>• Light and sound alarm</li> <li>• White light (LED) illuminator built-in : 2 LEDs</li> </ul>	...
Power supply	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 740 mA</li> </ul>	...
Power consumption	<ul style="list-style-type: none"> <li>• ≤ 10.3 W @ PoE</li> <li>• ≤ 8.9 W @ 12 V</li> </ul>	...
Housing	Dome - Metal	...
Color	White	Black



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

"Index of Protection"	IP67	IP20
Mechanical protection class	IK10	...
Operation temp	-30 °C ... 60 °C	...
Weight	0.73 kg	0.016 kg
Dimensions	Ø 126 x 105 mm	75 x 75 x 42 mm
Supported languages	Polish, English, Czech, French, Spanish, Dutch, German, Russian, Portuguese, Romanian, Ukrainian, Hungarian, Italian	...
Manufacturer / Brand	DAHUA	LEGRAND
Guarantee	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00